

### 226SML100M Information



For Reference Only

Part Number 226SML100M Manufacturer Illinois Capacitor

**Category** Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 22UF 20% 100V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 226SML100M Specifications

Manufacturer Part Number         226SML 100M           Manufacturer         Illinois Capacitor           Category         Capacitors           Package         Radial, Can - SMD           Series         SML           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         7.54 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         40°C ~ 85°C           Operating Temperature         Polar           Applications         General Purpose           Ripple Current - Low Frequency         120mA @ 120Hz           Ripple Current - High Frequency         180mA @ 100kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.417" (10.60mm)           Surface Mount Land Size         0.327" L x 0.327" W (8.30mm x 8.30mm)           Mounting Type         Surface Mount	<b>1</b>	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series SML Capacitance 22µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type  Capacitors Radial, Can - SMD Adminum Electrolytic Capacitors  SML  Actual Can - SMD  Swf C  2004  100V  2004  2004  2006  2007  2008  2	Manufacturer Part Number	226SML100M
Package         Radial, Can - SMD           Series         SML           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         7.54 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         120mA @ 120Hz           Ripple Current - High Frequency         180mA @ 100kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.417" (10.60mm)           Surface Mount Land Size         0.327" L x 0.327" W (8.30mm x 8.30mm)           Mounting Type         Surface Mount	Manufacturer	Illinois Capacitor
Package         Radial, Can - SMD           Series         SML           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         7.54 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         120mA @ 120Hz           Ripple Current - High Frequency         180mA @ 100kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.417" (10.60mm)           Surface Mount Land Size         0.327" L x 0.327" W (8.30mm x 8.30mm)           Mounting Type         Surface Mount	Category	Capacitors
Series         SML           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         7.54 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         120mA @ 120Hz           Ripple Current - High Frequency         180mA @ 100kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.417" (10.60mm)           Surface Mount Land Size         0.327" L x 0.327" W (8.30mm x 8.30mm)           Mounting Type         Surface Mount		Aluminum Electrolytic Capacitors
Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         7.54 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         120mA @ 120Hz           Ripple Current - High Frequency         180mA @ 100kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.417" (10.60mm)           Surface Mount Land Size         0.327" L x 0.327" W (8.30mm x 8.30mm)           Mounting Type         Surface Mount	Package	Radial, Can - SMD
Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)7.54 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency120mA @ 120HzRipple Current - High Frequency180mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.417" (10.60mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount	Series	SML
Voltage - Rated100VESR (Equivalent Series Resistance)7.54 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency120mA @ 120HzRipple Current - High Frequency180mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.417" (10.60mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount	Capacitance	22μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  120mA @ 120Hz  Ripple Current - High Frequency  180mA @ 100kHz  Impedance  Lead Spacing  -  Lead Spacing  -  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  7.54 Ohm @ 120Hz  2000 Hrs @ 85°C  -40°C ~ 85°C  Foliar  Foliar  -  General Purpose  120mA @ 120Hz  120mA @ 120Hz  180mA @ 100kHz  -  180mA @ 100kHz  -  180mA @ 100kHz  -  180mA @ 100kHz  -  Size / Dimension  0.315" Dia (8.00mm)  0.417" (10.60mm)  Surface Mount Land Size  0.327" L x 0.327" W (8.30mm x 8.30mm)	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  120mA @ 120Hz  Ripple Current - High Frequency  180mA @ 100kHz  Impedance  -  Lead Spacing  Size / Dimension  0.315" Dia (8.00mm)  Height - Seated (Max)  Surface Mount Land Size  0.327" L x 0.327" W (8.30mm x 8.30mm)  Mounting Type	Voltage - Rated	100V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 120mA @ 120Hz Rippedance - Lead Spacing Size / Dimension O.315" Dia (8.00mm) Height - Seated (Max) O.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type  -40°C ~ 85°C Robert - 40°C ~ 85°C Seneral Purpose General Purpose 120mA @ 120Hz 120mA @ 120Hz 180mA @ 100kHz 180m	ESR (Equivalent Series Resistance)	7.54 Ohm @ 120Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 120mA @ 120Hz  Ripple Current - High Frequency 180mA @ 100kHz  Impedance -  Lead Spacing -  Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.417" (10.60mm)  Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm)  Mounting Type Surface Mount	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  180mA @ 100kHz  Impedance  Lead Spacing  - Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  General Purpose  120mA @ 120Hz  180mA @ 100kHz  18	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  180mA @ 100kHz  Impedance  Lead Spacing  - Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  120mA @ 120Hz  180mA @ 100kHz  - 180mA	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  - Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  180mA @ 100kHz	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.417" (10.60mm)  Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm)  Mounting Type Surface Mount	Ripple Current - Low Frequency	120mA @ 120Hz
Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.417" (10.60mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount	Ripple Current - High Frequency	180mA @ 100kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.417" (10.60mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  0.417" (10.60mm)  0.327" L x 0.327" W (8.30mm x 8.30mm)  Mounting Type  Surface Mount	Lead Spacing	-
Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm)  Mounting Type Surface Mount	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Surface Mount	Height - Seated (Max)	0.417" (10.60mm)
	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)
	Mounting Type	Surface Mount
Package / Case Radial, Can - SMD	Package / Case	Radial, Can - SMD
Report errors?		Report errors?

#### 226SML100M Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 226SML100M Payment Methods



















### 226SML100M Shipping Methods













If you have any question about 226SML100M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com