

227CKE025MGM

227CKE025MGM Information

www.ceisener.com	Manufacturer Category	227CKE025MGM Illinois Capacitor Capacitors Aluminum Electrolytic Capacitors	
	Description Package	CAP ALUM 220UF 20% 25V RADIAL Radial, Can	
	i ucnuge	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



227CKE025MGM Specifications

ManufacturerIllinois CapacitorsCategoryCapacitorsAutinum Electrolytic CapacitorsPackageRadial, CanSeriesCKECapacitance220µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseKadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesCKECapacitance20µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency30mA @ 100kHzImpedance-Lead Spacing0.098° (2.50mm)Size / Dimension0.248° Dia (6.30mm)Height - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	227CKE025MGM
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesCKECapacitance220µFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency200m A @ 120HzRipple Current - High Frequency330m A @ 100kHzImpedance-Lead Spacing0.098° (2.50mm)Size / Dimension0.448° Dia (6.30mm)Height - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Illinois Capacitor
PackageRadial, CanSeriesCKECapacitance20µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRiple Current - Low Frequency300mA @ 120HzImpedance-Lad Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Category	Capacitors
SeriesCKECapacitance220µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200m A @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance220μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200MA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarrizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200mA @ 120HzBipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	СКЕ
Voltage - Rated25VESR (Equivalent Series Resistance)1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200mA @ 120HzBipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	220µF
ESR1.055 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200mA @ 120HzBipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200mA @ 120HzRipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	25V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200mA @ 120HzBipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	1.055 Ohm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency200mA @ 120HzRipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency200mA @ 120HzRipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency200mA @ 120HzRipple Current - High Frequency330mA @ 100kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	200mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	330mA @ 100kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

227CKE025MGM Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

227CKE025MGM Payment Methods



If you have any question about 227CKE025MGM, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com