

Heisener.com

227F Information

Part Number 227F

Manufacturer Hammond Manufacturing

Category Transformers

Power Transformers

Description XFRMR SEMI-TORO 5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









227F Specifications

Manufacturer Part Number 227F Manufacturer Hammond Manufacturing Category Transformers Package - Series 227 Type Semi-Toroidal Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 15V, Series 30V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation - Weight 0.38 lb (172.37g)		
Category Transformers Power Transformers Package - Series 227 Type Semi-Toroidal Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 15V, Series 30V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation -	Manufacturer Part Number	227F
Power Transformers	Manufacturer	Hammond Manufacturing
Package - Series 227 Type Semi-Toroidal Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 15V, Series 30V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation	Category	Transformers
Series 227 Type Semi-Toroidal Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 15V, Series 30V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation -		Power Transformers
Type Semi-Toroidal Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 15V, Series 30V Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation -	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Parallel 340mA, Series 170mA Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) Voltage - Isolation 115V Parallel 15V, Series 30V Parallel 340mA, Series 170mA Single Single Through No Power - Max 5 VA Through Hole 26.67mm -	Series	227
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Final Parallel 15V, Series 30V Parallel 340mA, Series 170mA Single Dual No Poul Through Through Po Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) Voltage - Isolation -	Туре	Semi-Toroidal
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 340mA, Series 170mA Single Dual Powar No 5 VA Powar Through Hole PC Pin 51.31mm L x 41.40mm W 26.67mm Voltage - Isolation -	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension51.31mm L x 41.40mm WHeight - Seated (Max)26.67mmVoltage - Isolation-	Voltage - Secondary (Full Load)	Parallel 15V, Series 30V
Secondary Winding(s)DualCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension51.31mm L x 41.40mm WHeight - Seated (Max)26.67mmVoltage - Isolation-	Current - Output (Max)	Parallel 340mA, Series 170mA
Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation -	Primary Winding(s)	Single
Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation -	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension51.31mm L x 41.40mm WHeight - Seated (Max)26.67mmVoltage - Isolation-	Center Tap	No
Termination Style PC Pin Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation -	Power - Max	5 VA
Size / Dimension 51.31mm L x 41.40mm W Height - Seated (Max) 26.67mm Voltage - Isolation -	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 26.67mm -	Termination Style	PC Pin
Voltage - Isolation -	Size / Dimension	51.31mm L x 41.40mm W
	Height - Seated (Max)	26.67mm
Weight 0.38 lb (172.37g)	Voltage - Isolation	-
	Weight	0.38 lb (172.37g)
Report errors?		Report errors?

227F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

227F Payment Methods



















227F Shipping Methods













If you have any question about 227F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com