

**228TTA025M Information**


www.heisener.com

For Reference Only

**Part Number** [228TTA025M](#)  
**Manufacturer** Illinois Capacitor  
**Category** Capacitors  
[Aluminum Electrolytic Capacitors](#)  
**Description** AXIAL E-CAP  
**Package** Axial, Can  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



Request a Quote

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**228TTA025M Specifications**

Manufacturer Part Number	<a href="#">228TTA025M</a>
Manufacturer	Illinois Capacitor
Category	Capacitors <a href="#">Aluminum Electrolytic Capacitors</a>
Package	Axial, Can
Series	TTA
Capacitance	2200µF
Tolerance	±20%
Voltage - Rated	25V
ESR (Equivalent Series Resistance)	143 mOhm @ 120Hz
Lifetime @ Temp.	2000 Hrs @ 85°C
Operating Temperature	-40°C ~ 85°C
Polarization	Polar
Applications	General Purpose
Ripple Current - Low Frequency	1.48A @ 120Hz
Ripple Current - High Frequency	1.8944A @ 50kHz
Impedance	-
Lead Spacing	-
Size / Dimension	0.630" Dia x 1.220" L (16.00mm x 31.00mm)
Height - Seated (Max)	-
Surface Mount Land Size	-
Mounting Type	Through Hole
Package / Case	Axial, Can

[Report errors?](#)

## 228TTA025M Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 228TTA025M Payment Methods



## 228TTA025M Shipping Methods



If you have any question about 228TTA025M, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)