



23012R1C8.25 Information

Heisener.com

Part Number 23012R1C8.25

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 230A 8.25KVAC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









23012R1C8.25 Specifications

Manufacturer Part Number 23012R1C8.25 Manufacturer Littelfuse Inc. Category Circuit Protection Flackage Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 230A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 230A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	23012R1C8.25
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 230A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating230AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating230AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating230AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 230A 8250V (8.25kV) - R 4250V (8.25kV) - - - - - - - - - - - - -	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8250V (8.25kV) - 8250V (8.25kV	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Case - Case Size / Dimension - Case - Case Size / Dimension - Case - Case	Current Rating	230A
Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Voltage Rating - AC	8250V (8.25kV)
Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Voltage Rating - DC	-
Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Response Time	-
Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Applications	Motor Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Class	R
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 15.875" L (76.20mm x 403.23mm)
		Report errors?

23012R1C8.25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

23012R1C8.25 Payment Methods



















23012R1C8.25 Shipping Methods













If you have any question about 23012R1C8.25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com