

2320092 Information



For Reference Only

Part Number 2320092

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description CONVERTER DC/DC 24VDC

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2320092 Specifications

Manufacturer Part Number 2320092 Manufacturer Phoenix Contact Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Quint Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)		
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Quint Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Manufacturer Part Number	2320092
Package Module Series Quint Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Manufacturer	Phoenix Contact
Package Module Series Quint Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series Quint Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)		DC DC Converters
Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Package	Module
Voltage - Input (Min) 18V Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Series	Quint
Voltage - Input (Max) 32V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Туре	Isolated
Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Voltage - Input (Min)	18V
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Voltage - Input (Max)	32V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Number of Outputs	1
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension -2000 August A	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications Operating Temperature -25°C ~ 60°C Efficiency Mounting Type DIN Rail Package / Case Module Size / Dimension 10A 240W 1TE (Commercial) -25°C ~ 60°C DIN Rail Package / Case Module 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 240W ITE (Commercial) -25°C ~ 60°C Module 14.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Current - Output (Max)	10A
Operating Temperature -25°C ~ 60°C Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Power (Watts)	240W
Efficiency 92% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Applications	ITE (Commercial)
Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Operating Temperature	-25°C ~ 60°C
Package / Case Module Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Efficiency	92%
Size / Dimension 4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)	Mounting Type	DIN Rail
	Package / Case	Module
Report errors?	Size / Dimension	4.92" L x 1.89" W x 5.12" H (125.0mm x 48.0mm x 130.0mm)
		Report errors?

2320092 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2320092 Payment Methods



















2320092 Shipping Methods













If you have any question about 2320092, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com