

2332-12-020 Information



For Reference Only

Part Number 2332-12-020 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY RF DPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2332-12-020 Specifications

| Manufacturer Part Number 2332-12-020 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 2300 Relay Type RF Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | | |
|--|--------------------------|-----------------------------|
| Category Relays Backage - Series 2300 Relay Type RF Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Manufacturer Part Number | 2332-12-020 |
| Package - Series 2300 Relay Type RF Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Manufacturer | Coto Technology |
| Package - Series 2300 Relay Type RF Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Category | Relays |
| Series 2300 Relay Type RF Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | | Signal Relays, Up to 2 Amps |
| Relay TypeRFCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin | Package | - |
| Coil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin | Series | 2300 |
| Coil Current12mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin | Relay Type | RF |
| Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Coil Type | Non Latching |
| Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Coil Current | 12mA |
| Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style | Coil Voltage | 12VDC |
| Switching Voltage Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 9 VDC 1 VDC 0.5ms Features 0.5ms Features Peatures Pe | Contact Form | DPST (2 Form A) |
| Turn On Voltage (Max) Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style | Contact Rating (Current) | 500mA |
| Turn Off Voltage (Min) Operate Time O.5ms Release Time O.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Switching Voltage | 200VAC, 200VDC - Max |
| Operate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin | Turn On Voltage (Max) | 9 VDC |
| Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Turn Off Voltage (Min) | 1 VDC |
| Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin | Operate Time | 0.5ms |
| Mounting Type Through Hole Termination Style PC Pin | Release Time | 0.15ms |
| Termination Style PC Pin | Features | Sealed - Hermetically |
| · | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

2332-12-020 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2332-12-020 Payment Methods



















2332-12-020 Shipping Methods













If you have any question about 2332-12-020, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com