

235-3019-02-0602

235-3019-02-0602 Information

Contract terror contract	Part Number Manufacturer Category Description Package	235-3019-02-0602 3M Connectors, Interconnects Sockets for ICs, Transistors CONN ZIG-ZAG ZIF 35POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	eference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



235-3019-02-0602 Specifications

Manufacturer3MCategoryConnectors, InterconnectsBackageSockets for ICs, TransistorsPackage-SeriesTextool?TypeZig-Zag, ZIF (ZIP)Number of Positions or Pins (Grid)35 (1 x 17, 1 x 18)Pich - Mating0.050" (1.27mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperPich - PostClosed FramePich - PostSolderContact Finish - PostGoldContact Finish - PostSpin (0.76µm)Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass Filled	•	
CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-SeriesTextool?TypeZig-Zag, ZIF (ZIP)Number of Positions or Pins (Grid)35 (1 x 17, 1 x 18)Pitch - Mating0.050° (1.27mm)Contact Finish - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.050° (1.27mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish PostGoldContact Finish - PostGoldContact Finish Thickness - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - PostGoldContact Finish Thickness - PostGolyContact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	235-3019-02-0602
Sockets for ICs, TransistorsPackage-SeriesTextool?TypeZig-Zag, ZIF (ZIP)Number of Positions or Pins (Grid)35 (1 x 17, 1 x 18)Pitch - Mating0.050" (1.27mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.050" (1.27mm)Contact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolderPitch - PostGoldContact Finish Thickness - PostSoluin (0.76µm)Contact Finish - PostGoldContact Finish - PostSolderContact Finish Thickness - PostSoluin (0.76µm)Contact Material - PostSoluin (0.76µm)Contact Material - PostSoluin (0.76µm)Contact Material - PostSoluin (0.76µm)Contact Material - PostSoluin CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Manufacturer	3M
Package-SeriesTextool?TypeZig-Zag, ZIF (ZIP)Number of Positions or Pins (Grid)35 (1 x 17, 1 x 18)Pitch - Mating0.050" (1.27mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.050" (1.27mm)Contact Finish - Post0.050" (1.27mm)Contact Finish - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish Thickness - PostSolderContact Finish Thickness - PostSoldir (1.27mm)Contact Finish Thickness - PostBeryllium CopperContact Finish Thickness - PostSoldir (1.27mm)Contact Finish Thickness - PostSoldir (1.27mm)Contact Material - PostSoldir (1.27mm)Contact Finish Thickness - PostSoldir (1.27mm)Contact Material - PostSoldir (1.27mm)Contact Finish Thickness - PostSoldir (1.27mm)Contact Material - PostSoldir (1.27mm)Housing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-S5°C ~ 125°C	Category	Connectors, Interconnects
SeriesTextool?TypeZig-Zag, ZIF (ZIP)Number of Positions or Pins (Grid)35 (1 x 17, 1 x 18)Pitch - Mating0.050" (1.27mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostSolderContact Finish Thickness - PostSoldin (0.76µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors
TypeZig-Zag, ZIF (ZIP)Number of Positions or Pins (Grid)35 (1 x 17, 1 x 18)Pitch - Mating0.050" (1.27mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostGoldContact Material - PostGoldContact Finish Thickness - PostSolyin (0.76µm)Contact Material - PostGoldContact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Package	-
Number of Positions or Pins (Grid)35 (1 x 17, 1 x 18)Pitch - Mating0.050" (1.27mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish Thickness - NostGoldContact Finish - PostO.050" (1.27mm)Contact Finish - PostGoldContact Finish Thickness - PostGoldContact Finish Thickness - PostBeryllium CopperHousing Material - PostBeryllium CopperPostPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Series	Textool?
Pitch - Mating0.050" (1.27mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Туре	Zig-Zag, ZIF (ZIP)
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish - Post30µin (0.76µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	35 (1 x 17, 1 x 18)
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.050" (1.27mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Mounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish Thickness - Post30μin (0.76μm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)
FeaturesClosed FrameTerminationSolderPitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish - Post30µin (0.76µm)Contact Finish Thickness - PostBeryllium CopperContact Material - PostPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper
TerminationSolderPitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Pitch - Post0.050" (1.27mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Features	Closed Frame
Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Post	0.050" (1.27mm)
Contact Material - PostBeryllium CopperHousing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Gold
Housing MaterialPolysulfone (PSU), Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	30µin (0.76µm)
Operating Temperature -55°C ~ 125°C	Contact Material - Post	Beryllium Copper
	Housing Material	Polysulfone (PSU), Glass Filled
Report errors?	Operating Temperature	-55°C ~ 125°C
		Report errors?

235-3019-02-0602 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

235-3019-02-0602 Payment Methods





If you have any question about 235-3019-02-0602, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com