

2362-05-000 Information

Heisener.com

Part Number 2362-05-000 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPDT 250MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2362-05-000 Specifications

Manufacturer Part Number 2362-05-000 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 2362 Relay Type Reed Coil Type Non Latching Coil Current 28.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing		
Category Relays Signal Relays, Up to 2 Amps Package - Series 2362 Relay Type Reed Coil Type Non Latching Coil Current 28.6mA Coil Voltage SVDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Manufacturer Part Number	2362-05-000
Package-Series2362Relay TypeReedCoil TypeNon LatchingCoil Current28.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface Mount	Manufacturer	Coto Technology
Package - Series 2362 Relay Type Reed Coil Type Non Latching Coil Current 28.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Category	Relays
Series 2362 Relay Type Reed Coil Type Non Latching Coil Current 28.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current28.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface Mount	Package	-
Coil TypeNon LatchingCoil Current28.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface Mount	Series	2362
Coil Current Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Release Time Sealed - Hermetically Mounting Type Surface Mount	Relay Type	Reed
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Coil Current	28.6mA
Contact Rating (Current) Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Coil Voltage	5VDC
Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Contact Rating (Current)	250mA
Turn Off Voltage (Min) Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount	Switching Voltage	100VAC, 100VDC - Max
Operate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface Mount	Turn On Voltage (Max)	3.8 VDC
Release Time2msFeaturesSealed - HermeticallyMounting TypeSurface Mount	Turn Off Voltage (Min)	0.4 VDC
Features Sealed - Hermetically Mounting Type Surface Mount	Operate Time	1.5ms
Mounting Type Surface Mount	Release Time	2ms
C 71	Features	Sealed - Hermetically
Termination Style Gull Wing	Mounting Type	Surface Mount
	Termination Style	Gull Wing
Report errors?		Report errors?

2362-05-000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2362-05-000 Payment Methods





















2362-05-000 Shipping Methods













If you have any question about 2362-05-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com