

2362-12-000 Information

Heisener.com

Part Number 2362-12-000 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPDT 250MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2362-12-000 Specifications

Manufacturer Part Number 2362-12-000 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 2362 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing		
CategoryRelaysPackage-Series2362Relay TypeReedCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	2362-12-000
Package-Series2362Relay TypeReedCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Coto Technology
Package - Series 2362 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Category	Relays
Series 2362 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Series	2362
Coil Current 12mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Reed
Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)250mASwitching Voltage100VAC, 100VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 250mA Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Coil Current	12mA
Contact Rating (Current) Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Coil Voltage	12VDC
Switching Voltage 100VAC, 100VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 1 VDC Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Contact Rating (Current)	250mA
Turn Off Voltage (Min) Operate Time 1.5ms Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	100VAC, 100VDC - Max
Operate Time1.5msRelease Time2msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	9 VDC
Release Time 2ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	1 VDC
Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	1.5ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	2ms
Termination Style Gull Wing	Features	Sealed - Hermetically
	Mounting Type	Surface Mount
D	Termination Style	Gull Wing
Report errors?		Report errors?

2362-12-000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2362-12-000 Payment Methods



















2362-12-000 Shipping Methods













If you have any question about 2362-12-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com