

### 2377-05-020 Information



For Reference Only

Part Number 2377-05-020 Manufacturer Coto Technology

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED DPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **2377-05-020 Specifications**

ManufacturerCoto TechnologyCategoryRelaysSignal Relays, Up to 2 AmpsPackage-Series2370Relay TypeReedCoil TypeNon LatchingCoil Current55.6mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)2.5 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-Series2370Relay TypeReedCoil TypeNon LatchingCoil Current55.6mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)2.5 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	2377-05-020
Package         -           Series         2370           Relay Type         Reed           Coil Type         Non Latching           Coil Current         55.6mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         2.5 VDC           Turn Off Voltage (Min)         0.4 VDC           Operate Time         0.5ms           Release Time         0.15ms           Features         Sealed - Hermetically           Mounting Type         Through Hole           Termination Style         PC Pin	Manufacturer	Coto Technology
Package         -           Series         2370           Relay Type         Reed           Coil Type         Non Latching           Coil Current         55.6mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         2.5 VDC           Turn Off Voltage (Min)         0.4 VDC           Operate Time         0.5ms           Release Time         0.15ms           Features         Sealed - Hermetically           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         2370           Relay Type         Reed           Coil Type         Non Latching           Coil Current         55.6mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         2.5 VDC           Turn Off Voltage (Min)         0.4 VDC           Operate Time         0.5ms           Release Time         0.15ms           Features         Sealed - Hermetically           Mounting Type         Through Hole           Termination Style         PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current55.6mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)2.5 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current55.6mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)2.5 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Series	2370
Coil Current 55.6mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 2.5 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.5ms Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)2.5 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.5msRelease Time0.15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 2.5 VDC  Turn Off Voltage (Min) 0.4 VDC  Operate Time 0.5ms  Release Time 0.15ms  Features Sealed - Hermetically  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	55.6mA
Contact Rating (Current)  Switching Voltage  200VAC, 200VDC - Max  Turn On Voltage (Max)  2.5 VDC  Turn Off Voltage (Min)  0.4 VDC  Operate Time  0.5ms  Release Time  0.15ms  Features  Sealed - Hermetically  Mounting Type  Through Hole  Termination Style  500mA  500mA	Coil Voltage	5VDC
Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 2.5 VDC  Turn Off Voltage (Min) 0.4 VDC  Operate Time 0.5ms  Release Time 0.15ms  Features Sealed - Hermetically  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  O.5ms  Release Time  O.15ms  Features  Sealed - Hermetically  Mounting Type  Through Hole  Termination Style  2.5 VDC  0.4 VDC  0.5ms  Sealed - Hermetically  Through Hole	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  0.5ms  Release Time  0.15ms  Features  Sealed - Hermetically  Mounting Type  Through Hole  Termination Style  O2.4 VDC  O5.5ms  Features  PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time 0.5ms  Release Time 0.15ms  Features Sealed - Hermetically  Mounting Type Through Hole  Termination Style PC Pin	Turn On Voltage (Max)	2.5 VDC
Release Time 0.15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.4 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.15ms
Termination Style PC Pin	Features	Sealed - Hermetically
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
report circus.		Report errors?

### 2377-05-020 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 2377-05-020 Payment Methods



















## 2377-05-020 Shipping Methods













If you have any question about 2377-05-020, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com