

Heisener.com

24-20 Information

Part Number 24-20

Manufacturer Signal Transformer Category Transformers

Power Transformers

Description XFRMR LAMINATED 480VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

com Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









24-20 Specifications

Manufacturer Part Number 24-20 Manufacturer Signal Transformer Category Transformers Package - Series - Type Laminated Core Voltage - Primary 105 V, 115 V, 125 V, 230 V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight 16 lbs (7.3kg)		
Category Transformers Power Transformers Package Series Type Laminated Core Voltage - Primary 105V, 115V, 125V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight	Manufacturer Part Number	24-20
Package - Series - Laminated Core Voltage - Primary 105V, 115V, 125V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight	Manufacturer	Signal Transformer
Package - Series - Type Laminated Core Voltage - Primary 105V, 115V, 125V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight	Category	Transformers
Series - Laminated Core Voltage - Primary 105V, 115V, 125V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight		Power Transformers
Type Laminated Core Voltage - Primary 105V, 115V, 125V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight 16 lbs (7.3kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 16 lbs (7.3kg)	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 12V, Series 24V Parallel 12V, Series 24V Parallel 12V, Series 24V Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight	Туре	Laminated Core
Current - Output (Max) Parallel 40A, Series 20A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 40A, Series 20A Single, Multiple Taps Yes Yes Yes Powal 180 VA 180 VA 180 VA 180 VA 190 VA	Voltage - Primary	105V, 115V, 125V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Single, Multiple Taps Dual Yes Solde Yes Yes Solder, Quick Connect 133.40mm L x 120.70mm W 111.10mm 1500Vrms 16 lbs (7.3kg)	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s) Center Tap Yes Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight	Current - Output (Max)	Parallel 40A, Series 20A
Center Tap Power - Max 480 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight Yes Analogous Allow All	Primary Winding(s)	Single, Multiple Taps
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight 16 lbs (7.3kg)	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight 16 lbs (7.3kg)	Center Tap	Yes
Termination Style Solder, Quick Connect Size / Dimension 133.40mm L x 120.70mm W Height - Seated (Max) 111.10mm Voltage - Isolation 1500Vrms Weight 16 lbs (7.3kg)	Power - Max	480 VA
Size / Dimension133.40mm L x 120.70mm WHeight - Seated (Max)111.10mmVoltage - Isolation1500VrmsWeight16 lbs (7.3kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Veight 111.10mm 1500Vrms 16 lbs (7.3kg)	Termination Style	Solder, Quick Connect
Voltage - Isolation 1500Vrms Weight 16 lbs (7.3kg)	Size / Dimension	133.40mm L x 120.70mm W
Weight 16 lbs (7.3kg)	Height - Seated (Max)	111.10mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	16 lbs (7.3kg)
		Report errors?

24-20 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

24-20 Payment Methods



















24-20 Shipping Methods













If you have any question about 24-20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com