

# 241-4-24A15

### 241-4-24A15 Information

Heisener.com	 241-4-24A15 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 6VA CHAS MOUNT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 241-4-24A15 Specifications

Manufacturer Part Number241-4-24A15Manufacturer APulse Electronics PowerCategoryTransformersPackage-PackageChassis-TranTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)SingleSecondary Winding(s)SingleSecondary Winding(s)SingleOwer - Max6 VAMounting TypeChassis MountTypinatrySider, Quick ConnectSize / DimensionSider, Quick ConnectSize / DimensionSidory Rum ManufactureVoltage - IsolationSidory Rum ManufactureSize / DimensionSidory Rum ManufactureWeight - Beated (Max)Sidory Rum ManufactureSider Quick ConnectSidory Rum ManufactureSider Alt (May)Sidory Rum ManufactureSize / DimensionGuters Sidory Rum ManufactureSider Quick ConnectSidory Rum ManufactureSider Alt (May)Sidory Rum ManufactureSider Alt (Sigory Rum Manufacture)Sidory Rum Manufactu		
CategoryTransformersPower TransformersPackage-SeriesChassis-TranTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)SingleSecondary Winding(s)SingleSecondary Winding(s)SinglePower - Max6 VAMounting TypeChassis MountSize / DimensionSolder, Quick ConnectSize / DimensionSolder, Quick ConnectSize / Dimension31.75mmHeight - Seated (Max)S00VrmsWeightSolder, Sales)	Manufacturer Part Number	241-4-24A15
InterfactPower TransformersPackage-SeriesChassis-TranTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)250mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountSize / DimensionSolder, Quick ConnectSize / Dimension31.75mmVoltage - Isolation2500VrmsWeight0.441b (199.58g)	Manufacturer	Pulse Electronics Power
Package-SeriesChassi-TranTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)SinglePrimary Winding(s)SingleCenter TapYesPower - MaxGlarque (ConnectMounting TypeSolder, Quick ConnectSter / DimensionSider, Quick ConnectSter / DimensionSider, Quick ConnectHeight - Seated (Max)31.75mmVoltage - IsolationStooVrmsWeight0.441 b(199.58g)	Category	Transformers
SeriesChassis-TranTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)SomAPrimary Winding(s)SingleSecondary Winding(s)YesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmWottge - IsolationSoloVrmsWeight0.44 lb (199.58g)		Power Transformers
TimeImmediateTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)250mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.441b (199.58g)	Package	-
Y115VVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)250mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeSolder, Quick ConnectTermination StyleSolder, Quick ConnectSize / Dimension31.75mmHeight - Seated (Max)3500VrmsVoltage - Isolation0.441b (199.58g)	Series	Chassis-Tran
Voltage - Secondary (Full Load)24VCurrent - Output (Max)250mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.441 b (199.58g)	Туре	Laminated Core
Current - Output (Max)250mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Current - Output (Max)	250mA
Center TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Primary Winding(s)	Single
Power - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Secondary Winding(s)	Single
Nounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Center Tap	Yes
Termination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Power - Max	6 VA
Size / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Mounting Type	Chassis Mount
Height - Seated (Max)31.75mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Termination Style	Solder, Quick Connect
Voltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Size / Dimension	60.45mm L x 35.05mm W
Weight 0.44 lb (199.58g)	Height - Seated (Max)	31.75mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.44 lb (199.58g)
		Report errors?

#### 241-4-24A15 Guarantees



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 241-4-24A15, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com