

241-4-28A16 Information

Heisener.com

Part Number 241-4-28A16

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 6VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









241-4-28A16 Specifications

Manufacturer Part Number 241-4-28A16 Manufacturer Pulse Electronics Power Category Transformers Power Transformers Power Transformers Package - Series Chassis-Tran Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 28V Current - Output (Max) 200mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)		
CategoryTransformersPackage-SeriesChassis-TranTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)200mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500Vrms	Manufacturer Part Number	241-4-28A16
Package - Series Chassis-Tran Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 28V Current - Output (Max) 200mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation Series	Manufacturer	Pulse Electronics Power
Package - Chassis-Tran Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 28V Current - Output (Max) 200mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation 2500Vrms	Category	Transformers
Series Chassis-Tran Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 28 V Current - Output (Max) 200mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation 28 SOOVrms		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 28V Current - Output (Max) 200mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation 28V	Package	-
Voltage - Primary Voltage - Secondary (Full Load) 28V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) Voltage - Isolation	Series	Chassis-Tran
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) Voltage - Isolation 28V 200mA 200mA Single Chassis Mount Chassis Mount 31.75mm 2500Vrms	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation 200mA Single Single Chassis Mount 6 VA Chassis Mount 6 VA Solder, Quick Connect 60.45mm L x 35.05mm W 31.75mm	Voltage - Primary	115V
Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 6 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) Voltage - Isolation Single Yes 2500Vrms	Voltage - Secondary (Full Load)	28V
Secondary Winding(s)SingleCenter TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500Vrms	Current - Output (Max)	200mA
Center TapYesPower - Max6 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500Vrms	Primary Winding(s)	Single
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation 2500Vrms	Secondary Winding(s)	Single
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation 2500Vrms	Center Tap	Yes
Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 35.05mm W Height - Seated (Max) 31.75mm Voltage - Isolation 2500Vrms	Power - Max	6 VA
Size / Dimension60.45mm L x 35.05mm WHeight - Seated (Max)31.75mmVoltage - Isolation2500Vrms	Mounting Type	Chassis Mount
Height - Seated (Max) 31.75mm Voltage - Isolation 2500Vrms	Termination Style	Solder, Quick Connect
Voltage - Isolation 2500Vrms	Size / Dimension	60.45mm L x 35.05mm W
-	Height - Seated (Max)	31.75mm
Weight 0.44 lb (199.58g)	Voltage - Isolation	2500Vrms
	Weight	0.44 lb (199.58g)
Report errors?		Report errors?

241-4-28A16 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

241-4-28A16 Payment Methods



















241-4-28A16 Shipping Methods













If you have any question about 241-4-28A16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com