

241-5-24L

241-5-24L Information

Heisener.com	241-5-24L Signal Transformer Transformers Power Transformers XFRMR LAMINATED 12VA CHAS MOUNT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



241-5-24L Specifications

Manufacturer Part Number241-5-24LManufacturerSignal TransformerCategoryTransformersPackage-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)SingleSecondary Winding(s)SingleSecondary Winding(s)SingleCurrent TapYesPower - Max12 VAMounting TypeChasis MountSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)2500VrmsWeightSionVrms		
CategoryTansformersPackage-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)500mAPrimary Winding(s)SingleSecondary Winding(s)SingleCurter TapYesPower - Max12 VAMounting TypeChassis MountSize / Dimension71.40mm Lx 36.30mm WHeight - Seated (Max)2500VrmsVoltage - Isolation2500VrmsWeight0.7 Ib (317.51g)	Manufacturer Part Number	241-5-24L
ImpersonancePackage-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)500mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max12 VAMounting TypeChasis MountSize / Dimension71.40mm Lx 36.30mm WSize / Dimension2300VrmsVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Manufacturer	Signal Transformer
Package-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)S00mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - MaxI2 VAMounting TypeChasis MountTermination StyleWire LeadsSize / Dimension71.40mn Lx 36.30mm WHeight - Seated (Max)2500VrmsWeightSingle	Category	Transformers
SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)500mAPrimary Winding(s)SingleSecondary Winding(s)YesPower - Max12 VAMounting TypeChasis MountTermination StyleYire LeadsSize / Dimension71.40mm Lx 36.30mm WHeight - Seated (Max)250VrmsWoltage - Isolation500VrmsWeight0.7 Ib (317.51g)		Power Transformers
TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)500mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)2500VrmsWoltage - Isolation0.7 Ib (317.51g)	Package	-
Yoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)500mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)2500VrmsWoitge - Isolation0.7 Ib (317.51g)	Series	Two-4-One?
Voltage - Secondary (Full Load)24VCurrent - Output (Max)500mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)2500VrmsVoltage - Isolation0.7 lb (317.51g)	Туре	Laminated Core
Current - Output (Max)500mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)2500VrmsVoltage - Isolation0.7 lb (317.51g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)2500VrmsVoltage - Isolation0.7 lb (317.51g)	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapYesPower - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension1.40mm L x 36.30mm WHeight - Seated (Max)42.80mmVoltage - Isolation500VrmsWeight0.7 lb (317.51g)	Current - Output (Max)	500mA
Center TapYesPower - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)42.80mmVoltage - Isolation500VrmsWeight0.7 lb (317.51g)	Primary Winding(s)	Single
Power - Max12 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)42.80mmVoltage - Isolation500VrmsWeight0.7 lb (317.51g)	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)42.80mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Center Tap	Yes
Termination StyleWire LeadsSize / Dimension71.40mm L x 36.30mm WHeight - Seated (Max)42.80mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Power - Max	12 VA
Size / Dimension 71.40mm L x 36.30mm W Height - Seated (Max) 42.80mm Voltage - Isolation 2500Vrms Weight 0.7 lb (317.51g)	Mounting Type	Chassis Mount
Height - Seated (Max)42.80mmVoltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Termination Style	Wire Leads
Voltage - Isolation2500VrmsWeight0.7 lb (317.51g)	Size / Dimension	71.40mm L x 36.30mm W
Weight 0.7 lb (317.51g)	Height - Seated (Max)	42.80mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.7 lb (317.51g)
		Report errors?

241-5-24L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 241-5-24L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com