

241-6-36A37 Information

Heisener.com

Part Number 241-6-36A37

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 30VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









241-6-36A37 Specifications

Manufacturer Part Number 241-6-36A37 Manufacturer Pulse Electronics Power Category Transformers Power Transformers Power Transformers Series Chassis-Tran Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 36V Current - Output (Max) 850mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)		
CategoryTransformersPackage-SeriesChassis-TranTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)36VCurrent - Output (Max)850mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Manufacturer Part Number	241-6-36A37
Package Power Transformers Chassis-Tran Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Size / Dimension Secondary Winding Secondary Winding Solder, Quick Connect Size / Dimension Solder, Quick Connect Solder, Quick Connect Size / Dimension Solder, Quick Connect Size / Dimension Solder, Quick Connect Solder, Quick Connect Size / Dimension Solder, Quick Connect Solder, Quick	Manufacturer	Pulse Electronics Power
Package-SeriesChassis-TranTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)36 VCurrent - Output (Max)850mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Category	Transformers
SeriesChassis-TranTypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)36 VCurrent - Output (Max)850mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 36V Current - Output (Max) 850mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 1.1 lbs (499g)	Series	Chassis-Tran
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) Voltage - Isolation Veight 850mA 850mA 850mA 860m Single Yes Songle Yes Solder, Quick Connect 82.55mm L x 49.28mm W 42.93mm Voltage - Isolation 1.1 lbs (499g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max 30 VA Mounting Type Chassis Mount Termination Style Size / Dimension Beight - Seated (Max) Voltage - Isolation Single Yes Yes Yes Yes Solder, Quick Connect 82.55mm L x 49.28mm W 42.93mm Voltage - Isolation 2500Vrms Unit libs (499g)	Voltage - Secondary (Full Load)	36V
Secondary Winding(s)SingleCenter TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	850mA
Center TapYesPower - Max30 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Primary Winding(s)	Single
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Secondary Winding(s)	Single
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Center Tap	Yes
Termination Style Solder, Quick Connect Size / Dimension 82.55mm L x 49.28mm W Height - Seated (Max) 42.93mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Power - Max	30 VA
Size / Dimension82.55mm L x 49.28mm WHeight - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Mounting Type	Chassis Mount
Height - Seated (Max)42.93mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Termination Style	Solder, Quick Connect
Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Size / Dimension	82.55mm L x 49.28mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	42.93mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

241-6-36A37 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

241-6-36A37 Payment Methods



















241-6-36A37 Shipping Methods













If you have any question about 241-6-36A37, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com