

241-8-28L

241-8-28L Information

Heisener.com Distai terice statistier	 241-8-28L Signal Transformer Transformers Power Transformers XFRMR LAMINATED 100VA CHAS MOUNT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



241-8-28L Specifications

Manufacturer Part Number241-8-28LManufacturerSignal TransformersCategoryTransformersPackage-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)SingleSecondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChaisi MountYendation StyleSize / DimensionSize / Dimension102.40mm Lx 58.50mm WHeight - Seated (Max)67.70mmWonter Seated (Max)Size / DimensionWonter Seated (Max)Size /		
CategoryTansformersPower TransformersPackage-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)100 VAPower - Max100 VAMounting TypeChasis MountSize / Dimension102.40mm Lx 58.50mm WBize / Dimension57.00mmVoltage - Isolation500Vrms	Manufacturer Part Number	241-8-28L
PackagePower TransformersPackage-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)100 VAPower - Max100 VAMounting TypeChassis MountSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)6.70mmVoltage - Isolation2500Vrms	Manufacturer	Signal Transformer
Package-SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)YesPower - Max100 VAPower - MaxChasis MountMounting TypeVir LeadsSize / Dimension102.40mm Lx 58.50mm WallBieght - Seated (Max)SioWrmsVoltage - Isolation250Vrms	Category	Transformers
SeriesTwo-4-One?TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChasis MountSize / Dimension102.40mm L x 58.50mm WSize / Dimension67.70mmVoltage - Isolation2500Vrms		Power Transformers
TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Package	-
AVoltage - Primary115VVoltage - Secondary (Full Load)28VCurrent - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)500Vrms	Series	Two-4-One?
Voltage - Secondary (Full Load)28VCurrent - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Туре	Laminated Core
Current - Output (Max)3.6APrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Voltage - Secondary (Full Load)	28V
Secondary Winding(s)SingleCenter TapYesPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Current - Output (Max)	3.6A
Center TapYesPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Primary Winding(s)	Single
Power - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Center Tap	Yes
Termination StyleWire LeadsSize / Dimension102.40mm L x 58.50mm WHeight - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Power - Max	100 VA
Size / Dimension 102.40mm L x 58.50mm W Height - Seated (Max) 67.70mm Voltage - Isolation 2500Vrms	Mounting Type	Chassis Mount
Height - Seated (Max)67.70mmVoltage - Isolation2500Vrms	Termination Style	Wire Leads
Voltage - Isolation 2500Vrms	Size / Dimension	102.40mm L x 58.50mm W
C .	Height - Seated (Max)	67.70mm
	Voltage - Isolation	2500Vrms
Weight 2.8 lbs (1.3kg)	Weight	2.8 lbs (1.3kg)
Report errors?		Report errors?

241-8-28L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 241-8-28L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com