

### **24114000021 Information**



For Reference Only

Part Number24114000021ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 4A 250VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 24114000021 Specifications

Manufacturer Part Number       24114000021         Manufacturer       Littelfuse Inc.         Category       Circuit Protection         Package       Cartridge, Non-Standard         Series       241         Fuse Type       Cartridge         Current Rating       4A         Voltage Rating - AC       250V         Voltage Rating - DC       -         Response Time       Medium         Applications       Electrical, Industrial         Features       Indicating         Class       -         Approvals       -         Operating Temperature       -25°C ~ 70°C         Breaking Capacity @ Rated Voltage       1.5kA         Mounting Type       Holder         Package / Case       Cartridge, Non-Standard         Size / Dimension       0.205" Dia x 0.984" L (5.20mm x 25.00mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Cartridge, Non-Standard  Series  241  Fuse Type  Cartridge  Current Rating  4A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Medium  Applications  Electrical, Industrial  Features  Indicating  Class  -  Approvals  -  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Sore Standard  Cartridge, Non-Standard  Sore Standard  Cartridge, Non-Standard  Sore Standard  Cartridge, Non-Standard  Sore Standard  Sor	Manufacturer Part Number	24114000021
PackageCartridge, Non-StandardSeries241Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC-Response TimeMediumApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-25°C ~ 70°CBreaking Capacity @ Rated Voltage1.5kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeries241Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC-Response TimeMediumApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-25°C ~ 70°CBreaking Capacity @ Rated Voltage1.5kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Category	Circuit Protection
Series 241  Fuse Type Cartridge  Current Rating 4A  Voltage Rating - AC 250V  Voltage Rating - DC -  Response Time Medium  Applications Electrical, Industrial  Features Indicating  Class -  Approvals -  Operating Temperature 2-25°C ~ 70°C  Breaking Capacity @ Rated Voltage 1.5kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 4A Voltage Rating - AC 250V  Voltage Rating - DC - Response Time Medium Applications Electrical, Industrial Features Indicating Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cartridge Cartridge  Cartridge Cartridge  Cartridge Cartridge  Cartridge  Cartridge  Cartridge  Cartridge  Cartridge  Cartridge  Cartridge  Cartridge  Cartridge  Coopenance  Cartridge  Cartridge  Cartridge  Cartridge  Cartridge  Coopenance  Cartridge	Package	Cartridge, Non-Standard
Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  Response Time  Medium  Applications  Electrical, Industrial  Features  Indicating  Class  -  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  4A  Mounting 44  A  Mounting 1000  Local 1000	Series	241
Voltage Rating - AC  Voltage Rating - DC  Response Time  Medium  Applications  Electrical, Industrial  Features  Indicating  Class  -  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Medium  Applications Electrical, Industrial  Features Indicating  Class -  Approvals -  Operating Temperature -25°C ~ 70°C  Breaking Capacity @ Rated Voltage 1.5kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Current Rating	4A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension  Medium Medium  Nellian  Flactrical, Industrial  1  Indicating  -  -  -  -  -  -  -  -  -  -  -  -  -	Voltage Rating - AC	250V
Applications  Electrical, Industrial  Features  Indicating  Class  - Approvals  Operating Temperature  Package / Case  Size / Dimension  Electrical, Industrial  Electrical, Industrial  Indicating  - Electrical, Industrial  Indicating  - Electrical, Industrial  Electrical (Industrial)  El	Voltage Rating - DC	-
Features Indicating  Class -  Approvals -  Operating Temperature -25°C ~ 70°C  Breaking Capacity @ Rated Voltage 1.5kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Response Time	Medium
Class - Approvals - Coperating Temperature -25°C ~ 70°C  Breaking Capacity @ Rated Voltage 1.5kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Applications	Electrical, Industrial
Approvals  Operating Temperature  -25°C ~ 70°C  Breaking Capacity @ Rated Voltage  1.5kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  O.205" Dia x 0.984" L (5.20mm x 25.00mm)	Features	Indicating
Operating Temperature  -25°C ~ 70°C  Breaking Capacity @ Rated Voltage  1.5kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Class	-
Breaking Capacity @ Rated Voltage 1.5kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Operating Temperature	-25°C ~ 70°C
Package / Case Cartridge, Non-Standard Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Breaking Capacity @ Rated Voltage	1.5kA
Size / Dimension 0.205" Dia x 0.984" L (5.20mm x 25.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.205" Dia x 0.984" L (5.20mm x 25.00mm)
		Report errors?

### **24114000021 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 24114000021 Payment Methods



















## 24114000021 Shipping Methods













If you have any question about 24114000021, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com