



24PCBFJ2G Information



For Reference Only

Part Number 24PCBFJ2G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR VACUUM GAUGE +-5 PSI

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









24PCBFJ2G Specifications

Manufacturer Part Number 24PCBFJ2G Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-DIP Module Series 24PC Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 115 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package - Report errors?		
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-DIP Module Series 24PC Pressure Type Compound Operating Pressure 5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 115 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.07" (1.78mm) Tube Port Style Features - Termination Style Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case July Module Supplier Device Package	Manufacturer Part Number	24PCBFJ2G
Package 4-DIP Module Series 24PC Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 115 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature +40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-DIP Module Series 24PC Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 115 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package -	Category	Sensors, Transducers
Series 24PC Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 115 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 115 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package -	Package	4-DIP Module
Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 115 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package -	Series	24PC
Output TypeWheatstone BridgeOutput0 mV ~ 115 mV (10V)Accuracy±1%Voltage - Supply10 V ~ 12 VPort SizeMale - 0.07" (1.78mm) TubePort StyleNeedleFeatures-Termination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-DIP ModuleSupplier Device Package-	Pressure Type	Compound
Output $0 \text{ mV} \sim 115 \text{ mV} (10 \text{V})$ Accuracy $\pm 1\%$ Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port Size $\text{Male} - 0.07'' (1.78 \text{mm}) \text{ Tube}$ Port Style Needle Features - Termination Style PC Pin Maximum Pressure $\pm 20 \text{ PSI} (\pm 137.9 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-DIP Module Supplier Device Package $-40^{\circ}\text{C} \sim 40^{\circ}\text{C} \sim 40^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Operating Pressure	±5 PSI (±34.47 kPa)
Accuracy $\pm 1\%$ Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.07''$ (1.78mm) TubePort StyleNeedleFeatures-Termination StylePC PinMaximum Pressure $\pm 20 \text{ PSI}$ ($\pm 137.9 \text{ kPa}$)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-DIP Module Supplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply10 V ~ 12 VPort SizeMale - 0.07" (1.78mm) TubePort StyleNeedleFeatures-Termination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-DIP ModuleSupplier Device Package-	Output	$0 \text{ mV} \sim 115 \text{ mV} (10\text{V})$
Port Size Male - 0.07 " (1.78 mm) Tube Port Style Needle Features - Termination Style PC Pin Maximum Pressure ± 20 PSI (± 137.9 kPa) Operating Temperature ± 40 °C ~ 85 °C Package / Case ± 4 -DIP Module Supplier Device Package	Accuracy	±1%
Port Style Features - Termination Style Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package -	Voltage - Supply	10 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure ± 20 PSI (± 137.9 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case	Port Size	Male - 0.07" (1.78mm) Tube
Termination StylePC PinMaximum Pressure ± 20 PSI (± 137.9 kPa)Operating Temperature -40° C ~ 85° CPackage / Case 4 -DIP ModuleSupplier Device Package-	Port Style	Needle
Maximum Pressure ± 20 PSI (± 137.9 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-DIP Module Supplier Device Package $-$	Features	-
Operating Temperature -40°C ~ 85°C Package / Case 4-DIP Module Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-DIP Module Supplier Device Package -	Maximum Pressure	±20 PSI (±137.9 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-DIP Module
Report errors?	Supplier Device Package	-
_		Report errors?

24PCBFJ2G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

24PCBFJ2G Payment Methods



















24PCBFJ2G Shipping Methods













If you have any question about 24PCBFJ2G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com