



24PCDFM1G Information

Heisener.com

Part Number 24PCDFM1G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE20PC24PC 30 PSI

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









24PCDFM1G Specifications

Manufacturer Part Number24PCDFM1GManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP ModuleSeries24PCPressure TypeCompoundOperating Pressure±30 PSI (±206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 330 mV (10V)Accuracy±1%Voltage - Supply10 V ~ 12 VPort SizeMale - 1/4" (6.35mm) UNFPort StyleThreadedFeatures-Termination StylePC PinMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-Report errors?		
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP Module Series 24PC Pressure Type Compound Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 330 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 1/4" (6.35mm) UNF Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Manufacturer Part Number	24PCDFM1G
Package 4-SIP Module Series 24PC Pressure Type Compound Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 330 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 1/4" (6.35mm) UNF Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature +40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series 24PC Pressure Type Compound Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 330 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 1/4" (6.35mm) UNF Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Category	Sensors, Transducers
Series 24PC Pressure Type Compound Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 330 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 1/4" (6.35mm) UNF Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Compound Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 330 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 1/4" (6.35mm) UNF Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module
Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 330 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 1/4" (6.35mm) UNF Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Series	24PC
Output Type Output Outp	Pressure Type	Compound
Output $0 \text{ mV} \sim 330 \text{ mV} (10 \text{ V})$ Accuracy $\pm 1\%$ Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port Size $Male - 1/4$ " $(6.35 \text{mm}) \text{ UNF}$ Port Style $Threaded$ Features - Termination Style $PC \text{ Pin}$ Maximum Pressure $\pm 60 \text{ PSI} (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package $-$	Operating Pressure	±30 PSI (±206.84 kPa)
Accuracy $\pm 1\%$ Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) UNFPort StyleThreadedFeatures-Termination StylePC PinMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port Size $\text{Male - 1/4" (6.35 mm) UNF}$ Port Style Threaded Features $-$ Termination Style PC Pin Maximum Pressure $\pm 60 \text{ PSI (}\pm 413.69 \text{ kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package	Output	0 mV ~ 330 mV (10V)
Port Size Male - 1/4" (6.35mm) UNF Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Accuracy	±1%
Port Style Threaded Features - Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Voltage - Supply	10 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure ± 60 PSI (± 413.69 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case	Port Size	Male - 1/4" (6.35mm) UNF
Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Port Style	Threaded
Maximum Pressure ± 60 PSI (± 413.69 kPa)Operating Temperature -40° C ~ 85° CPackage / Case 4 -SIP ModuleSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±60 PSI (±413.69 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

24PCDFM1G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

24PCDFM1G Payment Methods





















24PCDFM1G Shipping Methods













If you have any question about 24PCDFM1G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com