



24PCEFA6G Information



For Reference Only

Part Number 24PCEFA6G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 0.5PSI GAUGE

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









24PCEFA6G Specifications

Manufacturer Part Number 24PCEFA6G Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SIP Module Series 24PC Pressure Type Compound Operating Pressure ±0.5 PSI (±3.45 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 35 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.2" (5mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - Report errors?		
CategorySensors, TransducersPackage4-SIP ModuleSeries24PCPressure TypeCompoundOperating Pressure±0.5 PSI (±3.45 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 35 mV (10V)Accuracy±1%Voltage - Supply10 V ~ 12 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	24PCEFA6G
Package 4-SIP Module Series 24PC Pressure Type Compound Operating Pressure ±0.5 PSI (±3.45 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 35 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.2" (5mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature +40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series 24PC Pressure Type Compound Operating Pressure ±0.5 PSI (±3.45 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 35 mV (10V) Accuracy ±1% Voltage - Supply 10 V ~ 12 V Port Size Male - 0.2" (5mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Category	Sensors, Transducers
Series24PCPressure TypeCompoundOperating Pressure±0.5 PSI (±3.45 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 35 mV (10V)Accuracy±1%Voltage - Supply10 V ~ 12 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeCompoundOperating Pressure±0.5 PSI (±3.45 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 35 mV (10V)Accuracy±1%Voltage - Supply10 V ~ 12 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Package	4-SIP Module
Operating Pressure $\pm 0.5 \text{ PSI } (\pm 3.45 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 35 \text{ mV } (10 \text{ V})$ Accuracy $\pm 1\%$ Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.2 " (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Series	24PC
Output TypeWheatstone BridgeOutput0 mV ~ 35 mV (10V)Accuracy±1%Voltage - Supply10 V ~ 12 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Pressure Type	Compound
Output $0 \text{ mV} \sim 35 \text{ mV} (10\text{V})$ Accuracy $\pm 1\%$ Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.2 " (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $\pm 20 \text{ PSI} (\pm 137.9 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Operating Pressure	±0.5 PSI (±3.45 kPa)
Accuracy $\pm 1\%$ Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.2 " (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply $10 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.2" (5mm) TubePort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package-	Output	0 mV ~ 35 mV (10V)
Port Size Male - 0.2" (5mm) Tube Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Accuracy	±1%
Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Voltage - Supply	10 V ~ 12 V
Features - Comparison Style PC Pin PC Pin PC PSI ($\pm 137.9 \text{ kPa}$) Operating Temperature $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Package / Case $\pm 4-\text{SIP Module}$ Supplier Device Package -	Port Size	Male - 0.2" (5mm) Tube
Termination StylePC PinMaximum Pressure ± 20 PSI (± 137.9 kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package-	Port Style	Barbless
Maximum Pressure ± 20 PSI (± 137.9 kPa)Operating Temperature -40° C ~ 85° CPackage / Case 4 -SIP ModuleSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±20 PSI (±137.9 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

24PCEFA6G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

24PCEFA6G Payment Methods

































If you have any question about 24PCEFA6G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com