

250E2C5.5

Request a Quote

250E2C5.5 Information

	Heisener.com	Part Number	250E2C5.5
		Manufacturer	Littelfuse Inc.
		Category	Circuit Protection Electrical, Specialty Fuses
		Description	FUSE CRTRDGE 250A 5.5KVAC NONSTD
		Package	Cartridge, Non-Standard
			For the pricing/inventory/lead time, please contact
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



250E2C5.5 Specifications

Manufacturer Part Number250E2C5.5ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating250AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-ApplicationsTransformer ProtectionFacturesIndicatingClassEApprovals-Operating Temperature-ApprovalsStokAMouning TypeHolderFackage / CaseCartridge, Non-StandardSize / Dimension15875" Lx 3.000" Wx 6.380" H (403.23mm x 76.20mm x 162.05mm)			
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent RatingS00N (5.5kV)Voltage Rating - AC500V (5.5kV)Voltage Rating - DC-ApplicationsFransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature0kAMounting TypeHolderAutong TypeStore, Store,	Manufacturer Part Number	250E2C5.5	
Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating250AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1587s" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.	
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingOperating Temperature-Operating Temperature80KAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.85'' L x 3.000'' W x 6.380'' H (403.23mm x 76.20mm x 162.05mm)	Category	Circuit Protection	
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating250AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature80kAMounting TypeBolkaPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)		Electrical, Specialty Fuses	
Fuse Type Cartridge Fuse Type Cartridge Current Rating 250A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature 80kA Mounting Type Bolder Package / Case Cartridge, Non-Standard Fizer / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard	
Current Rating250AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Series	POWR-GARD?	
Voltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Fuse Type	Cartridge	
Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Current Rating	250A	
Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Voltage Rating - AC	5500V (5.5kV)	
ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Voltage Rating - DC	-	
FeaturesIndicatingFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Response Time	-	
ClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Applications	Transformer Protection	
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Features	Indicating	
Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Class	Е	
Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Approvals	-	
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Operating Temperature	-	
Package / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	80kA	
Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Mounting Type	Holder	
	Package / Case	Cartridge, Non-Standard	
Report errors?	Size / Dimension	15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	
		Report errors?	

250E2C5.5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 250E2C5.5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com