

250LLE3R3MEFCT16.3X11

250LLE3R3MEFCT16.3X11 Information



For Reference Only

Part Number 250LLE3R3MEFCT16.3X11

Manufacturer Rubycon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3.3UF 20% 250V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









250LLE3R3MEFCT16.3X11 Specifications

Manufacturer Part Number 250LLE3R3MEFCT16.3X11 Manufacturer Rubycon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series LLE Capacitance 3.3µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	*	
Category Capacitors Package Radial, Can Series LLE Capacitance 3.3µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Oplarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	250LLE3R3MEFCT16.3X11
Package Radial, Can Series LLE Capacitance 3.3µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Rubycon
Package Radial, Can Series LLE Capacitance 3.3µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series LLE Capacitance 3.3µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 3.3μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Raistance) 12000 Hrs @ 105°C - Constitute of 12000 Hrs @ 105°C - 40°C ~ 105°C	Series	LLE
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency42mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	3.3μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 12000 Hrs @ 105°C -40°C ~ 105°	Voltage - Rated	250V
Operating Temperature -40°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	12000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency 42mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	-
Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	42mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

250LLE3R3MEFCT16.3X11 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

250LLE3R3MEFCT16.3X11 Payment Methods



















250LLE3R3MEFCT16.3X11 Shipping Methods













If you have any question about 250LLE3R3MEFCT16.3X11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com