

250LSQ470MEFC36X50

250LSQ470MEFC36X50 Information



For Reference Only

Part Number 250LSQ470MEFC36X50

Manufacturer Rubycon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 250V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









250LSQ470MEFC36X50 Specifications

Manufacturer Part Number 250LSQ470MEFC36X50 Manufacturer Rubycon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LSQ Capacitance 470μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series LSQ Capacitance 470μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	250LSQ470MEFC36X50
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals LSQ Capacitance 470µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization -Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance Lead Spacing 0.500" (12.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can - Screw Terminals	Manufacturer	Rubycon
PackageRadial, Can - Screw TerminalsSeriesLSQCapacitance470μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.888A @ 10kHzImpedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)2.126" (54.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series LSQ Capacitance 470μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 470μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	LSQ
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.888A @ 10kHzImpedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)2.126" (54.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	250V
Operating Temperature -25°C ~ 85°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	3000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.888A @ 10kHz Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	-
Ripple Current - High Frequency Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)2.126" (54.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	1.6A @ 120Hz
Lead Spacing0.500" (12.70mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)2.126" (54.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	1.888A @ 10kHz
Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 2.126" (54.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.500" (12.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	1.417" Dia (36.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	2.126" (54.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

250LSQ470MEFC36X50 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

250LSQ470MEFC36X50 Payment Methods



















250LSQ470MEFC36X50 Shipping Methods













If you have any question about 250LSQ470MEFC36X50, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com