



250R18W334KV4E Information



For Reference Only

Part Number 250R18W334KV4E

Manufacturer Johanson Dielectrics Inc.

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.33UF 25V X7R 1206

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









250R18W334KV4E Specifications

Manufacturer Part Number 250R18W334KV4E Manufacturer Johanson Dielectrics Inc. Category Capacitors Package 1206 (3216 Metric) Series TANCERAM? Capacitance 0.33µF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -		
Category Capacitors Package 1206 (3216 Metric) Series TANCERAM? Capacitance 0.33µF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Manufacturer Part Number	250R18W334KV4E
Package 1206 (3216 Metric) Series TANCERAM? Capacitance 0.33μF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Manufacturer	Johanson Dielectrics Inc.
Package 1206 (3216 Metric) Series TANCERAM? Capacitance 0.33µF Tolerance ±10% Voltage - Rated 25 V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Category	Capacitors
Series TANCERAM? Capacitance 0.33μF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -		Ceramic Capacitors
Capacitance 0.33µF Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Package	1206 (3216 Metric)
Tolerance ±10% Voltage - Rated 25V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications SMPS Filtering Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) Thickness (Max) 0.070" (1.78mm) Lead Spacing	Series	TANCERAM?
Voltage - Rated25VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.125" L x 0.062" W (3.17mm x 1.57mm)Height - Seated (Max)-Thickness (Max)0.070" (1.78mm)Lead Spacing-	Capacitance	0.33μF
Temperature CoefficientX7ROperating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Features-Ratings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.125" L x 0.062" W (3.17mm x 1.57mm)Height - Seated (Max)-Thickness (Max)0.070" (1.78mm)Lead Spacing-	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Voltage - Rated	25V
Features - Ratings - Applications SMPS Filtering SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Temperature Coefficient	X7R
Ratings - SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications SMPS Filtering Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Applications	SMPS Filtering
Package / Case 1206 (3216 Metric) Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.125" L x 0.062" W (3.17mm x 1.57mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.070" (1.78mm) -	Package / Case	1206 (3216 Metric)
Thickness (Max) 0.070" (1.78mm) Lead Spacing -	Size / Dimension	0.125" L x 0.062" W (3.17mm x 1.57mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.070" (1.78mm)
Lead Style	Lead Spacing	-
Lead Style	Lead Style	-
Report errors?		Report errors?

250R18W334KV4E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

250R18W334KV4E Payment Methods



















250R18W334KV4E Shipping Methods













If you have any question about 250R18W334KV4E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com