



### 251R14S560FV4T Information



For Reference Only

Part Number 251R14S560FV4T

Manufacturer Johanson Technology Inc.

**Category** Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 56PF 250V NP0 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 251R14S560FV4T Specifications

Manufacturer Part Number         251R14S560FV4T           Manufacturer         Johanson Technology Inc.           Category         Capacitors           Package         0603 (1608 Metric)           Series         S           Capacitance         56pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.062" L x 0.032" W (1.57mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.89mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         0603 (1608 Metric)           Series         S           Capacitance         56pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.062" L x 0.032" W (1.57mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.89mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	251R14S560FV4T
Package         0603 (1608 Metric)           Series         S           Capacitance         56pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.062" L x 0.032" W (1.57mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.89mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Johanson Technology Inc.
Package         0603 (1608 Metric)           Series         S           Capacitance         56pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.062" L x 0.032" W (1.57mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.89mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         S           Capacitance         56pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.062" L x 0.032" W (1.57mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.89mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance       56pF         Tolerance       ±1%         Voltage - Rated       250V         Temperature Coefficient       COG, NPO         Operating Temperature       -55°C ~ 125°C         Features       High Q, Low Loss         Ratings       -         Applications       RF, Microwave, High Frequency         Failure Rate       -         Mounting Type       Surface Mount, MLCC         Package / Case       0603 (1608 Metric)         Size / Dimension       0.062" L x 0.032" W (1.57mm x 0.81mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.89mm)         Lead Spacing       -         Lead Style       -	Package	0603 (1608 Metric)
Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.062" L x 0.032" W (1.57mm x 0.81mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.89mm)           Lead Spacing         -           Lead Style         -	Series	S
Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.062" L x 0.032" W (1.57mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.89mm)Lead Spacing-Lead Style-	Capacitance	56pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Tolerance	±1%
Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Voltage - Rated	250V
Features High Q, Low Loss  Ratings - RF, Microwave, High Frequency  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0603 (1608 Metric)  Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm)  Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm)  Lead Spacing - Lead Style - Company of the state of	Temperature Coefficient	C0G, NP0
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case       0603 (1608 Metric)         Size / Dimension       0.062" L x 0.032" W (1.57mm x 0.81mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.89mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.062" L x 0.032" W (1.57mm x 0.81mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.89mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.035" (0.89mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.062" L x 0.032" W (1.57mm x 0.81mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.89mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 251R14S560FV4T Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 251R14S560FV4T Payment Methods



















# 251R14S560FV4T Shipping Methods













If you have any question about 251R14S560FV4T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com