



251S48W105KV4E Information

Heisener.com

Part Number 251S48W105KV4E

Manufacturer Johanson Dielectrics Inc.

Category Capacitors

Ceramic Capacitors

Description MLCC 2225,1.0?F,10%,250V

Package 2225 (5763 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









251S48W105KV4E Specifications

Manufacturer Part Number 251848W105KV4E Manufacturer Johanson Dielectrics Inc. Category Capacitors Package 2225 (5763 Metric) Series - Capacitance 1µF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -		
Category Capacitors Package 2225 (5763 Metric) Series - Capacitance 1μF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Manufacturer Part Number	251S48W105KV4E
Package 2225 (5763 Metric) Series - Capacitance 1μF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Manufacturer	Johanson Dielectrics Inc.
Package 2225 (5763 Metric) Series - Capacitance 1μF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 1μF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 1μF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Package	2225 (5763 Metric)
Tolerance ±10% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated250VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2225 (5763 Metric)Size / Dimension0.225" L x 0.250" W (5.72mm x 6.35mm)Height - Seated (Max)-Thickness (Max)0.140" (3.55mm)Lead Spacing-Lead Style-	Capacitance	1μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X7R A7R A7R A7R A7R - 55°C ~ 125°C - Sor ~ 125°C - Sur-Acceptor - Control - - APPLICATION - - - - - - - - - - - - -	Tolerance	±10%
Operating Temperature Features -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension Height - Seated (Max) - Thickness (Max) Lead Spacing Lead Style	Voltage - Rated	250V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 2225 (5763 Metric) Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.225" L x 0.250" W (5.72mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	2225 (5763 Metric)
Thickness (Max) 0.140" (3.55mm) Lead Spacing - Lead Style -	Size / Dimension	0.225" L x 0.250" W (5.72mm x 6.35mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.140" (3.55mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

251S48W105KV4E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

251S48W105KV4E Payment Methods



















251S48W105KV4E Shipping Methods













If you have any question about 251S48W105KV4E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com