

## 25E1C15.5 Information

heisener.com

Part Number 25E1C15.5

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 25A 1.55KVAC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **25E1C15.5 Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  POWR-GARD?  Fuse Type  Cartridge  Current Rating  25A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Transformer Protection  Features  Indicating  Class  E  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Littelfuse Inc.  Littelfuse Inc.  Circuit Protection  Electrical, Specialty Fuses  Cartridge, Non-Standard  3.000" Dia x 18.875" L (76.20mm x 479.43mm)		
Category Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 25A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals Class E Approvals Cheating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension  Circuit Protection  Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension  Circuit Protection  Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	25E1C15.5
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series POWR-GARD?  Fuse Type Cartridge  Current Rating 25A  Voltage Rating - AC 1550V (1.55kV)  Voltage Rating - DC -  Response Time -  Applications Transformer Protection  Features Indicating  Class E  Approvals -  Operating Temperature -  Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 3 2500 Cartridge, Non-Standard  Size / Dimension 3 2500 Cartridge, Non-Standard  Size / Dimension 3 2000" Dia x 18.875" L (76.20mm x 479.43mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC1550V (1.55kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC1550V (1.55kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 18.875" L (76.20mm x 479.43mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC1550V (1.55kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  25A 1550V (1.55kV) - 1650V (1.55kV) - 16	Series	POWR-GARD?
Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Transformer Protection  Features  Indicating  Class  E  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  1550V (1.55kV)  -  0-  80W (1.55kV)  -  Capacity @ Rated Voltage  Bow (1.55kV)  -  Capacity (1.5c) (1.5c)  -  Capaci	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard Size / Dimension - Size / Dimension - Cartridge, Non-Standard - Cartridge, Non-Standard	Current Rating	25A
Response Time Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension  Transformer Protection	Voltage Rating - AC	1550V (1.55kV)
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Transformer Protection Indicating E B.  Reaking Capacity @ Rated Voltage Holder Cartridge, Non-Standard 3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Voltage Rating - DC	-
Features Indicating  Class E  Approvals -  Operating Temperature -  Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Applications	Transformer Protection
Approvals Operating Temperature	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  80kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Class	E
Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 3.000" Dia x 18.875" L (76.20mm x 479.43mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 18.875" L (76.20mm x 479.43mm)
*		Report errors?

### 25E1C15.5 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 25E1C15.5 Payment Methods





















### 25E1C15.5 Shipping Methods













If you have any question about 25E1C15.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com