



25ET116-S-G Information

Heisener.com

Part Number 25ET116-S-G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 4A 28V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









25ET116-S-G Specifications

Manufacturer Part Number 25ET116-S-G Manufacturer Honeywell Sensing and Productivity Solutions Category Switches Package - Series ET Circuit SPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold		
CategorySwitchesPackage-SeriesETCircuitSPDTSwitch FunctionOn-MomCurrent Rating4A (DC)Voltage Rating - AC-Voltage Rating - DC28VActuator TypeLocking LeverActuator Length25.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionEnvironment SealedFeaturesMagnetic Hold	Manufacturer Part Number	25ET116-S-G
Toggle Switches Package Series ET Circuit SPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Locking Lever Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Environment Sealed Features Magnetic Hold	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Circuit SPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Type, Color - Illumination Voltage (Nominal) - Monting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Monting Con-Monting SpDT SPDT SpDT Sealed SpDT Sealed SpDT SpDT Sealed SpDT SpDT SpDT SpDT SpDT SpDT SpDT SpDT	Category	Switches
SeriesETCircuitSPDTSwitch FunctionOn-MomCurrent Rating4A (DC)Voltage Rating - AC-Voltage Rating - DC28VActuator TypeLocking LeverActuator Length25.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionEnvironment SealedFeaturesMagnetic Hold		Toggle Switches
Circuit SPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Package	-
Switch Function Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Environment Sealed Features Magnetic Hold	Series	ET
Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Environment Sealed Magnetic Hold	Switch Function	On-Mom
Voltage Rating - DC28VActuator TypeLocking LeverActuator Length25.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionEnvironment SealedFeaturesMagnetic Hold	Current Rating	4A (DC)
Actuator Type Locking Lever 25.90mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Voltage Rating - AC	-
Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Actuator Type	Locking Lever
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Actuator Length	25.90mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Illumination Type, Color	-
Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Termination Style	Screw Terminal
Ingress Protection Environment Sealed Features Magnetic Hold	Panel Cutout Dimensions	Circular - 12.40mm Dia
Features Magnetic Hold	Bushing Thread	15/32-32
·	Ingress Protection	Environment Sealed
Report errors?	Features	Magnetic Hold
		Report errors?

25ET116-S-G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

25ET116-S-G Payment Methods



















25ET116-S-G Shipping Methods













If you have any question about 25ET116-S-G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com