

25LET Information



For Reference Only

Part Number 25LET Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 25A 240VAC/150VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









25LET Specifications

Manufacturer Part Number 25LET Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series LET Fuse Type Cartridge Current Rating 25A Voltage Rating - AC 240V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm) Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLETFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Manufacturer Part Number	25LET
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLETFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesLETFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Category	Circuit Protection
Series LET Fuse Type Cartridge Current Rating 25A Voltage Rating - AC 240V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Carter 1000 240V Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Capacity & Ce, UR Operating Temperature - Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 240V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 25A 240V 240V 240V 240V 240V 240V 26B 26C 26C 26C 27C 28C 28C 28C 28C 28C 28C 29C 20C 20C 20C 20C 20C 20C 20	Series	LET
Voltage Rating - AC Voltage Rating - DC 150V Response Time Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 240V 240V 240V 240V 240V 240V 260V Beletrical, Industrial - CE, UR - CE, UR CYLING CYLING	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 150V 150V 150V 150V 150V 150V 150V 150	Current Rating	25A
Response Time - Applications Electrical, Industrial Features - Class - CE, UR Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Voltage Rating - AC	240V
Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Voltage Rating - DC	150V
Features - Class - CE, UR Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Response Time	-
Class - CE, UR Operating Temperature - Sereaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, UR CUR CUR CUR CUR CON CON CON CON CON CON CON CO	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Approvals	CE, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.697" Dia x 1.032" L (17.70mm x 26.20mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.697" Dia x 1.032" L (17.70mm x 26.20mm)
		Report errors?

25LET Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

25LET Payment Methods



















25LET Shipping Methods













If you have any question about 25LET, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com