

25MXC8200MEFCSN20X40

25MXC8200MEFCSN20X40 Information



For Reference Only

Part Number 25MXC8200MEFCSN20X40

Manufacturer Rubycon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 8200UF 20% 25V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









25MXC8200MEFCSN20X40 Specifications

Manufacturer Part Number 25MXC8200MEFCSN20X40 Manufacturer Rubycon Category Capacitors Package Radial, Can - Snap-In Series MXC Capacitance 8200μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization -
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series MXC Capacitance 8200 μ F Tolerance $\pm 20\%$ Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
PackageRadial, Can - Snap-InSeriesMXCCapacitance $8200μF$ Tolerance $±20%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 Hrs @ 105°C$ Operating Temperature $-40°C \sim 105°C$
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Capacitance $8200\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $3000 \text{ Hrs } @ 105 ^{\circ}\text{C}$ Operating Temperature $-40 ^{\circ}\text{C} \sim 105 ^{\circ}\text{C}$
Tolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance) - Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -3000 Hrs @ 105°C -40°C ~ 105°C
Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Polarization -
Applications General Purpose
Ripple Current - Low Frequency 2.34A @ 120Hz
Ripple Current - High Frequency 2.691A @ 10kHz
Impedance -
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.787" Dia (20.00mm)
Height - Seated (Max) 1.654" (42.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report error

25MXC8200MEFCSN20X40 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

25MXC8200MEFCSN20X40 Payment Methods



















25MXC8200MEFCSN20X40 Shipping Methods













If you have any question about 25MXC8200MEFCSN20X40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com