

25TQC22MYFT

25TQC22MYFT Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



25TQC22MYFT Specifications

Manufacturer Part Number 25TQC22MYFT Manufacturer Panasonic Electronic Components Category Capacitors Category Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Package 2917 (7343 Metric) Series POSCAP? TQC Capacitance 22µF Tolerance ±20% Voltage - Rated 25V Type Molded Derating Temperature 70 mOhm Operating Temperature 2000 Hrs @ 105°C Lifetime @ Temp. 2017 (7343 Metric) Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287° L x 0.169° W (7.30mm x 4.30mm) Height - Seated (Max) 0.59° (1.50mm) Lead Spacing - Height - Seated (Max) 0.059° (1.50mm) Lead Spacing 515 Features General Purpose		
CategoryCapacitorsTantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TQCCapacitance22µFTolerance±20%Voltage - Rated25VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FaturesD15FeaturesGeneral Purpose	Manufacturer Part Number	25TQC22MYFT
Initialum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TQCCapacitance22µFTolerance±20%Voltage - Rated25VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max).059" (1.50mm)Lead Spacing-FacturesD15FeaturesGeneral Purpose	Manufacturer	Panasonic Electronic Components
Package2917 (7343 Metric)SeriesPOSCAP? TQCCapacitance22µFTolerance±20%Voltage - Rated25VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FeaturesD15FeaturesGeneral Purpose	Category	Capacitors
Series POSCAP? TQC Capacitance 22µF Tolerance ±20% Voltage - Rated 25V Type Molded ESR (Equivalent Series Resistance) 70 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.0287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.059" (1.50mm) Lead Spacing - Features D15 Features General Purpose		Tantalum - Polymer Capacitors
Capacitance22µFTolerance±20%Voltage - Rated25∨TypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FeaturesD15FeaturesGeneral Purpose	Package	2917 (7343 Metric)
Tolerance±20%Voltage - Rated25VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-FeaturesD15FeaturesGeneral Purpose	Series	POSCAP? TQC
Note Interference Voltage - Rated 25V Type Molded ESR (Equivalent Series Resistance) 70 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.059" (1.50mm) Lead Spacing - Manufacturer Size Code D15 Features General Purpose	Capacitance	22µF
TypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	Tolerance	±20%
A70 mOhmESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	Voltage - Rated	25V
Operating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	Туре	Molded
Lifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	70 mOhm
And the second	Operating Temperature	-55°C ~ 105°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	Lifetime @ Temp.	2000 Hrs @ 105°C
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	Mounting Type	Surface Mount
Height - Seated (Max)0.059" (1.50mm)Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeD15FeaturesGeneral Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeD15FeaturesGeneral Purpose	Height - Seated (Max)	0.059" (1.50mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	D15
Report errors?	Features	General Purpose
		Report errors?

25TQC22MYFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

25TQC22MYFT Payment Methods





If you have any question about 25TQC22MYFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com