

Heisener.com

### **260E Information**

Part Number 260E

Manufacturer Hammond Manufacturing

**Category** Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 80VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **260E Specifications**

Manufacturer Part Number         260E           Manufacturer         Hammond Manufacturing           Category         Transformers           Package         -           Series         260           Type         Laminated Core           Voltage - Primary         100V, 120V, 220V, 240V           Voltage - Secondary (Full Load)         450V, 6.3V, 5V           Current - Output (Max)         115mA, 3A, 2A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Triple           Center Tap         Yes           Power - Max         80 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         76.20mm L x 77.72mm W           Height - Seated (Max)         64.26mm           Voltage - Isolation         -           Weight         3.4 lbs (1.5kg)		
Category Package Package Package Power Transformers  Series Package Power Transformers  260  Type Laminated Core Voltage - Primary 100V, 120V, 220V, 240V  Voltage - Secondary (Full Load) 450V, 6.3V, 5V  Current - Output (Max) 115mA, 3A, 2A  Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Triple Center Tap Yes Power - Max 80 VA  Mounting Type Chassis Mount  Termination Style Size / Dimension 76.20mm L x 77.72mm W  Height - Seated (Max) Voltage - Isolation  Transformers  100V, 120V, 220V, 240V  450V, 6.3V, 5V  Current - Output (Max) 115mA, 3A, 2A  Primary Winding(s) Dual, Multiple Taps  Yes  Power - Max 80 VA  64.26mm Voltage - Isolation	Manufacturer Part Number	260E
Package         -           Series         260           Type         Laminated Core           Voltage - Primary         100V, 120V, 220V, 240V           Voltage - Secondary (Full Load)         450V, 6.3V, 5V           Current - Output (Max)         115mA, 3A, 2A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Triple           Center Tap         Yes           Power - Max         80 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         76.20mm L x 77.72mm W           Height - Seated (Max)         64.26mm           Voltage - Isolation         -	Manufacturer	Hammond Manufacturing
Package-Series260TypeLaminated CoreVoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)450V, 6.3V, 5VCurrent - Output (Max)115mA, 3A, 2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)TripleCenter TapYesPower - Max80 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension76.20mm L x 77.72mm WHeight - Seated (Max)64.26mmVoltage - Isolation-	Category	Transformers
Series         260           Type         Laminated Core           Voltage - Primary         100V, 120V, 220V, 240V           Voltage - Secondary (Full Load)         450V, 6.3V, 5V           Current - Output (Max)         115mA, 3A, 2A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Triple           Center Tap         Yes           Power - Max         80 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         76.20mm L x 77.72mm W           Height - Seated (Max)         64.26mm           Voltage - Isolation         -		Power Transformers
Type Laminated Core  Voltage - Primary 100V, 120V, 220V, 240V  Voltage - Secondary (Full Load) 450V, 6.3V, 5V  Current - Output (Max) 115mA, 3A, 2A  Primary Winding(s) Dual, Multiple Taps  Secondary Winding(s) Triple  Center Tap Yes  Power - Max 80 VA  Mounting Type Chassis Mount  Termination Style Wire Leads  Size / Dimension 76.20mm L x 77.72mm W  Height - Seated (Max) 64.26mm  Voltage - Isolation -	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  450V, 6.3V, 5V  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Center Tap  Yes  Power - Max  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  76.20mm L x 77.72mm W  Height - Seated (Max)  Voltage - Isolation  100V, 120V, 220V, 240V  450V, 6.3V, 5V  Dual, Multiple Taps  Triple  Yes  Powal Secondary Winding(s)  Triple  Chassis Mount  Chassis Mount  76.20mm L x 77.72mm W  64.26mm	Series	260
Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Center Tap  Power - Max  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  450V, 6.3V, 5V  115mA, 3A, 2A  Dual, Multiple Taps  Triple  Yes  Powal Av  Yes  Chassis Mount  Chassis Mount  Termination Style  Wire Leads  64.26mm  Voltage - Isolation  -	Type	Laminated Core
Current - Output (Max)  Primary Winding(s)  Dual, Multiple Taps  Secondary Winding(s)  Triple  Center Tap  Yes  Power - Max  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  115mA, 3A, 2A  115mA, 3A,	Voltage - Primary	100V, 120V, 220V, 240V
Primary Winding(s)  Secondary Winding(s)  Triple  Center Tap  Yes  Power - Max  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Dual, Multiple Taps  Triple  Yes  Yes  Yes  Power  Yes  Wire Leads  76.20mm L x 77.72mm W  64.26mm  -	Voltage - Secondary (Full Load)	450V, 6.3V, 5V
Secondary Winding(s)TripleCenter TapYesPower - Max80 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension76.20mm L x 77.72mm WHeight - Seated (Max)64.26mmVoltage - Isolation-	Current - Output (Max)	115mA, 3A, 2A
Center TapYesPower - Max80 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension76.20mm L x 77.72mm WHeight - Seated (Max)64.26mmVoltage - Isolation-	Primary Winding(s)	Dual, Multiple Taps
Power - Max  Mounting Type Chassis Mount  Termination Style Wire Leads  Size / Dimension 76.20mm L x 77.72mm W  Height - Seated (Max) 64.26mm  Voltage - Isolation -	Secondary Winding(s)	Triple
Mounting Type Chassis Mount Wire Leads Size / Dimension 76.20mm L x 77.72mm W Height - Seated (Max) 64.26mm Voltage - Isolation -	Center Tap	Yes
Termination Style Wire Leads Size / Dimension 76.20mm L x 77.72mm W Height - Seated (Max) 64.26mm Voltage - Isolation -	Power - Max	80 VA
Size / Dimension 76.20mm L x 77.72mm W Height - Seated (Max) 64.26mm Voltage - Isolation -	Mounting Type	Chassis Mount
Height - Seated (Max)  Voltage - Isolation  64.26mm  -	Termination Style	Wire Leads
Voltage - Isolation -	Size / Dimension	76.20mm L x 77.72mm W
	Height - Seated (Max)	64.26mm
Weight 3.4 lbs (1.5kg)	Voltage - Isolation	-
	Weight	3.4 lbs (1.5kg)
Report errors?		Report errors?

### **260E Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **260E Payment Methods**





















## **260E Shipping Methods**













If you have any question about 260E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com