

## **2610-12-310 Information**

Heisener.com

Part Number 2610-12-310 Manufacturer Coto Technology

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED SPDT 200MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2610-12-310 Specifications

Manufacturer Part Number         2610-12-310           Manufacturer         Coto Technology           Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         2600           Relay Type         Reed           Coil Type         Non Latching           Coil Current         -           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         200mA           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         9 VDC           Turn Off Voltage (Min)         1 VDC           Operate Time         -           Release Time         -           Features         -           Mounting Type         Through Hole		
Category         Relays           Package         -           Series         2600           Relay Type         Reed           Coil Type         Non Latching           Coil Current         -           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         200mA           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         9 VDC           Turn Off Voltage (Min)         1 VDC           Operate Time         -           Release Time         -           Features         -           Mounting Type         Through Hole	Manufacturer Part Number	2610-12-310
Package-Series2600Relay TypeReedCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)200mASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Manufacturer	Coto Technology
Package - Series 2600 Relay Type Reed Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 200mA Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Through Hole	Category	Relays
Series 2600 Relay Type Reed Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 200mA Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)200mASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)200mASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Series	2600
Coil Current Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 200mA Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time Release Time - Release Time - Features Mounting Type Through Hole	Relay Type	Reed
Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)200mASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time-Release Time-Features-Mounting TypeThrough Hole	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 200mA Switching Voltage 250VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole	Coil Current	-
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  1 VDC  Operate Time  -  Release Time  -  Features  -  Mounting Type  7 Through Hole	Coil Voltage	12VDC
Switching Voltage  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  1 VDC  Operate Time  Release Time  -  Features  Mounting Type  250VAC - Max  9 VDC  1 VDC  Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  7 Urn Off Voltage (Min)  9 VDC  1 VDC  Operate Time  -  Release Time  -  Features  Mounting Type  7 Through Hole	Contact Rating (Current)	200mA
Turn Off Voltage (Min)  Operate Time - Release Time - Features - Mounting Type  1 VDC - Through Hole	Switching Voltage	250VAC - Max
Operate Time - Release Time - Compared to the Peatures - Compared to the Peatures - Compared to the Peatures Through Hole - Compared to the Peature Through Hole	Turn On Voltage (Max)	9 VDC
Release Time - Features - Mounting Type Through Hole	Turn Off Voltage (Min)	1 VDC
Features - Mounting Type Through Hole	Operate Time	-
Mounting Type Through Hole	Release Time	-
	Features	-
Towningtion Style	Mounting Type	Through Hole
remination style PC PIn	Termination Style	PC Pin
Report errors?		Report errors?

### **2610-12-310 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **2610-12-310 Payment Methods**



















# 2610-12-310 Shipping Methods













If you have any question about 2610-12-310, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com