

2611-12-311 Information

Heisener.com

Part Number 2611-12-311 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPDT 250MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2611-12-311 Specifications

Manufacturer Part Number 2611-12-311 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 2600 Relay Type Reed Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin		
Category Relays Backage - Series 2600 Relay Type Reed Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	2611-12-311
Package Series 2600 Relay Type Reed Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 1 VDC Operate Time Release Time Features Mounting Type Through Hole Termination Style Series 2600 Reed 2000	Manufacturer	Coto Technology
Package - Series 2600 Relay Type Reed Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series 2600 Relay Type Reed Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)250mASwitching Voltage200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Series	2600
Coil Current - Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style 12VDC	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	-
Contact Rating (Current) Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time Release Time - Release Time - Features Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time Release Time - Features Mounting Type Through Hole Termination Style	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Retures Mounting Type Through Hole Termination Style 9 VDC 1 VDC - 1 VDC - Through Hole PC Pin	Contact Rating (Current)	250mA
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Through Hole Termination Style 1 VDC - Through Hole PC Pin	Switching Voltage	200VDC - Max
Operate Time - Release Time	Turn On Voltage (Max)	9 VDC
Release Time	Turn Off Voltage (Min)	1 VDC
Features - Mounting Type Through Hole PC Pin	Operate Time	-
Mounting Type Through Hole Termination Style PC Pin	Release Time	-
Termination Style PC Pin	Features	-
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

2611-12-311 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2611-12-311 Payment Methods



















2611-12-311 Shipping Methods













If you have any question about 2611-12-311, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com