



26ET101-S-G Information

Heisener.com

Part Number 26ET101-S-G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 4A 28V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









26ET101-S-G Specifications

Manufacturer Part Number 26ET101-S-G Manufacturer Honeywell Sensing and Productivity Solutions Category Switches Package - Series ET Circuit DPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold		
CategorySwitchesPackage-SeriesETCircuitDPDTSwitch FunctionOn-MomCurrent Rating4A (DC)Voltage Rating - AC-Voltage Rating - DC28VActuator TypeLocking LeverActuator Length25.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionEnvironment SealedFeaturesMagnetic Hold	Manufacturer Part Number	26ET101-S-G
Toggle Switches Package - Series ET Circuit DPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Locking Lever Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Fermination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Environment Sealed Magnetic Hold	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Series ET Circuit DPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Category	Switches
SeriesETCircuitDPDTSwitch FunctionOn-MomCurrent Rating4A (DC)Voltage Rating - AC-Voltage Rating - DC28VActuator TypeLocking LeverActuator Length25.90mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionEnvironment SealedFeaturesMagnetic Hold		Toggle Switches
Circuit DPDT Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Package	-
Switch Function On-Mom Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Series	ET
Current Rating 4A (DC) Voltage Rating - AC - Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Environment Sealed Magnetic Hold	Switch Function	On-Mom
Voltage Rating - DC Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Environment Sealed Features Magnetic Hold	Current Rating	4A (DC)
Actuator Type Locking Lever Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Voltage Rating - AC	-
Actuator Length 25.90mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Actuator Type	Locking Lever
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Actuator Length	25.90mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Illumination Type, Color	-
Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection Environment Sealed Features Magnetic Hold	Termination Style	Screw Terminal
Ingress Protection Environment Sealed Features Magnetic Hold	Panel Cutout Dimensions	Circular - 12.40mm Dia
Features Magnetic Hold	Bushing Thread	15/32-32
	Ingress Protection	Environment Sealed
Report errors?	Features	Magnetic Hold
		Report errors?

26ET101-S-G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

26ET101-S-G Payment Methods



















26ET101-S-G Shipping Methods













If you have any question about 26ET101-S-G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com