



## **26PCAFG6G Information**



For Reference Only

Part Number 26PCAFG6G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESSURE SENSOR GAUGE =/-1.0 PSI

Package 8-SMD Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **26PCAFG6G Specifications**

Manufacturer Part Number26PCAFG6GManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPressure Sensors, TransducersPackage8-SMD ModuleSeries26PCPressure TypeVented GaugeOperating Pressure±1 PSIOutput TypeWheatstone BridgeOutput0 mV ~ 16.7 mV (10V)Accuracy±0.5%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.09" (2.4mm) Tube, DualPort StyleBarbed	
Category  Sensors, Transducers  Pressure Sensors, Transducers  Package  8-SMD Module  Series  26PC  Pressure Type  Vented Gauge  Operating Pressure  ±1 PSI  Output Type  Wheatstone Bridge  Output  0 mV ~ 16.7 mV (10V)  Accuracy  ±0.5%  Voltage - Supply  Port Size  Male - 0.09" (2.4mm) Tube, Dual	
Pressure Sensors, Transducers  Package 8-SMD Module  Series 26PC  Pressure Type Vented Gauge  Operating Pressure ±1 PSI  Output Type Wheatstone Bridge  Output 0 mV ~ 16.7 mV (10V)  Accuracy ±0.5%  Voltage - Supply 2.5 V ~ 16 V  Port Size Male - 0.09" (2.4mm) Tube, Dual	
Package 8-SMD Module  Series 26PC  Pressure Type Vented Gauge  Operating Pressure ±1 PSI  Output Type Wheatstone Bridge  Output 0 mV ~ 16.7 mV (10V)  Accuracy ±0.5%  Voltage - Supply 2.5 V ~ 16 V  Port Size Male - 0.09" (2.4mm) Tube, Dual	
Series 26PC  Pressure Type Vented Gauge  Operating Pressure ±1 PSI  Output Type Wheatstone Bridge  Output 0 mV ~ 16.7 mV (10V)  Accuracy ±0.5%  Voltage - Supply 2.5 V ~ 16 V  Port Size Male - 0.09" (2.4mm) Tube, Dual	
Pressure TypeVented GaugeOperating Pressure $\pm 1$ PSIOutput TypeWheatstone BridgeOutput $0$ mV ~ $16.7$ mV ( $10$ V)Accuracy $\pm 0.5\%$ Voltage - Supply $2.5$ V ~ $16$ VPort SizeMale - $0.09$ " ( $2.4$ mm) Tube, Dual	
Operating Pressure $\pm 1$ PSI Output Type Wheatstone Bridge Output $0 \text{ mV} \sim 16.7 \text{ mV} (10\text{V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size Male - $0.09$ " (2.4mm) Tube, Dual	
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 16.7 \text{ mV} (10\text{V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - $0.09$ " (2.4mm) Tube, Dual	
Output $0 \text{ mV} \sim 16.7 \text{ mV} (10 \text{V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size Male - $0.09$ " (2.4mm) Tube, Dual	
Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size Male - $0.09$ " (2.4mm) Tube, Dual	
Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size Male - $0.09$ " (2.4mm) Tube, Dual	
Port Size Male - 0.09" (2.4mm) Tube, Dual	
Port Style Barbed	
Features Temperature Compensated	
Termination Style Solder Pad	
Maximum Pressure ±20 PSI (±137.9 kPa)	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Package / Case 8-SMD Module	
Supplier Device Package 8-SMD	
Report et	rors?

#### **26PCAFG6G Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **26PCAFG6G Payment Methods**





















## **26PCAFG6G Shipping Methods**













If you have any question about 26PCAFG6G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com