



26PCBFJ3G Information

Heisener.com

Part Number 26PCBFJ3G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE20PC26PC 5 PSI

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









26PCBFJ3G Specifications

Manufacturer 26PCBFJ3G Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 50 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male ~ 0.07" (1.78mm) Tube Port Style Needle Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	_	
Category Sensors, Transducers Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 50 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Manufacturer Part Number	26PCBFJ3G
Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 50 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Category	Sensors, Transducers
Series26PCPressure TypeCompoundOperating Pressure±5 PSI (±34.47 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 50 mV (10V)Accuracy±0.5%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.07" (1.78mm) TubePort StyleNeedleFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP		Pressure Sensors, Transducers
Pressure Type Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 50 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module
Operating Pressure ±5 PSI (±34.47 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 50 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Series	26PC
Output TypeWheatstone BridgeOutput0 mV ~ 50 mV (10V)Accuracy±0.5%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.07" (1.78mm) TubePort StyleNeedleFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±20 PSI (±137.9 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP	Pressure Type	Compound
Output $0 \text{ mV} \sim 50 \text{ mV} (10\text{V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - $0.07'' (1.78\text{mm})$ TubePort StyleNeedleFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 20 \text{ PSI} (\pm 137.9 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package $4-\text{SIP}$	Operating Pressure	±5 PSI (±34.47 kPa)
Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.07 " (1.78 mm) TubePort StyleNeedleFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package 4-SIP	Output Type	Wheatstone Bridge
Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output	$0 \text{ mV} \sim 50 \text{ mV} (10 \text{V})$
Port Size Male - 0.07" (1.78mm) Tube Port Style Needle Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Accuracy	$\pm 0.5\%$
Port Style Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±20 PSI (±137.9 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Voltage - Supply	2.5 V ~ 16 V
FeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure ± 20 PSI (± 137.9 kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP ModuleSupplier Device Package 4-SIP	Port Size	Male - 0.07" (1.78mm) Tube
Termination StylePC PinMaximum Pressure ± 20 PSI (± 137.9 kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package 4-SIP	Port Style	Needle
Maximum Pressure ± 20 PSI (± 137.9 kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package 4-SIP	Features	Temperature Compensated
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package 4-SIP	Maximum Pressure	±20 PSI (±137.9 kPa)
Supplier Device Package 4-SIP	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Domont owners?	Supplier Device Package	4-SIP
Report errors?		Report errors?

26PCBFJ3G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

26PCBFJ3G Payment Methods



















26PCBFJ3G Shipping Methods













If you have any question about 26PCBFJ3G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com