



26PCCFB6G Information



For Reference Only

Part Number 26PCCFB6G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 15PSI GAUGE

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









26PCCFB6G Specifications

| Manufacturer 26PCCFB6G Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - | | |
|--|--------------------------|--|
| CategorySensors, TransducersPackage4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±15 PSI (±103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.5%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.18" (4.57mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±45 PSI (±310.26 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package- | Manufacturer Part Number | 26PCCFB6G |
| Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - | Manufacturer | Honeywell Sensing and Productivity Solutions |
| Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - | Category | Sensors, Transducers |
| Series26PCPressure TypeCompoundOperating Pressure±15 PSI (±103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.5%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.18" (4.57mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±45 PSI (±310.26 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package- | | Pressure Sensors, Transducers |
| Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package | Package | 4-SIP Module |
| Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package | Series | 26PC |
| Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.5%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.18" (4.57mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±45 PSI (±310.26 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package- | Pressure Type | Compound |
| Output $0 \text{ mV} \sim 100 \text{ mV} (10\text{V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.18 " (4.57mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 45 \text{ PSI} (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package- | Operating Pressure | ±15 PSI (±103.42 kPa) |
| Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package | Output Type | Wheatstone Bridge |
| Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package | Output | $0 \text{ mV} \sim 100 \text{ mV} (10 \text{V})$ |
| Port Size Male - 0.18" (4.57mm) Tube Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - | Accuracy | ±0.5% |
| Port Style Barbed Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package | Voltage - Supply | 2.5 V ~ 16 V |
| Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package | Port Size | Male - 0.18" (4.57mm) Tube |
| Termination Style PC Pin Maximum Pressure $\pm 45 \text{ PSI } (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package - | Port Style | Barbed |
| Maximum Pressure ± 45 PSI $(\pm 310.26$ kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package $-$ | Features | Temperature Compensated |
| Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - | Termination Style | PC Pin |
| Package / Case 4-SIP Module Supplier Device Package - | Maximum Pressure | ±45 PSI (±310.26 kPa) |
| Supplier Device Package - | Operating Temperature | -40°C ~ 85°C |
| | Package / Case | 4-SIP Module |
| Report errors? | Supplier Device Package | - |
| Report chois. | | Report errors? |

26PCCFB6G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

26PCCFB6G Payment Methods



















26PCCFB6G Shipping Methods













If you have any question about 26PCCFB6G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com