



26PCCFK2G Information

Heisener.com

Part Number 26PCCFK2G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR VACUUM GAUGE +-15 PSI

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









26PCCFK2G Specifications

Manufacturer Part Number26PCCFK2GManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-DIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±15 PSI (±103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.5%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±45 PSI (±310.26 kPa)Operating Temperature-40°C ~ 85°C		
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-DIP Module Series 26PC Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature	Manufacturer Part Number	26PCCFK2G
Package 4-DIP Module Series 26PC Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-DIP Module Series 26PC Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature	Category	Sensors, Transducers
Series $26PC$ Pressure TypeCompoundOperating Pressure $\pm 15 \text{ PSI } (\pm 103.42 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 100 \text{ mV } (10\text{ V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.2 " (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 45 \text{ PSI } (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$		Pressure Sensors, Transducers
Pressure Type Compound Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.5% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±45 PSI (±310.26 kPa) Operating Temperature -40°C ~ 85°C	Package	4-DIP Module
Operating Pressure $\pm 15 \text{ PSI } (\pm 103.42 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 100 \text{ mV } (10\text{V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.2 " (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 45 \text{ PSI } (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Series	26PC
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 100 \text{ mV} (10\text{V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.2 " (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 45 \text{ PSI} (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Pressure Type	Compound
Output $0 \text{ mV} \sim 100 \text{ mV} (10 \text{ V})$ Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size $\text{Male} - 0.2'' (5.08 \text{mm}) \text{ Tube}$ Port Style Barbless Features $\text{Temperature Compensated}$ Termination Style PC Pin Maximum Pressure $\pm 45 \text{ PSI } (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Pressure	±15 PSI (±103.42 kPa)
Accuracy $\pm 0.5\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size $\text{Male - 0.2" (5.08mm) Tube}$ Port Style Barbless Features $\text{Temperature Compensated}$ Termination Style PC Pin Maximum Pressure $\pm 45 \text{ PSI } (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Output Type	Wheatstone Bridge
Voltage - Supply 2.5 V \sim 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ± 45 PSI (± 310.26 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Output	$0 \text{ mV} \sim 100 \text{ mV} (10 \text{V})$
Port Size Male - 0.2 " (5.08 mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ± 45 PSI (± 310.26 kPa) Operating Temperature ± 40 °C ~ 85 °C	Accuracy	±0.5%
Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ± 45 PSI (± 310.26 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Supply	2.5 V ~ 16 V
FeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure ± 45 PSI (± 310.26 kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Port Size	Male - 0.2" (5.08mm) Tube
Termination Style PC Pin Maximum Pressure ± 45 PSI (± 310.26 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Port Style	Barbless
Maximum Pressure $\pm 45 \text{ PSI } (\pm 310.26 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Features	Temperature Compensated
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Termination Style	PC Pin
	Maximum Pressure	±45 PSI (±310.26 kPa)
	Operating Temperature	-40°C ~ 85°C
Package / Case 4-DIP Module	Package / Case	4-DIP Module
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

26PCCFK2G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

26PCCFK2G Payment Methods



















26PCCFK2G Shipping Methods













If you have any question about 26PCCFK2G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com