



26PCDFA6G Information

www.heisener.com

For Reference Only

Part Number 26PCDFA6G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 30PSI GAUGE

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









26PCDFA6G Specifications

Manufacturer Part Number26PCDFA6GManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±30 PSI (±206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.2%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-Report errors?		
CategorySensors, TransducersPackage4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±30 PSI (±206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.2%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	26PCDFA6G
Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure	Manufacturer	Honeywell Sensing and Productivity Solutions
Package4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±30 PSI (±206.84 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.2%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Category	Sensors, Transducers
Series 26PC Pressure Type Compound Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.2% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -		Pressure Sensors, Transducers
Pressure TypeCompoundOperating Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 100 \text{ mV } (10\text{ V})$ Accuracy $\pm 0.2\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.2 " (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Package	4-SIP Module
Operating Pressure ±30 PSI (±206.84 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.2% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Series	26PC
Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.2%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Pressure Type	Compound
Output $0 \text{ mV} \sim 100 \text{ mV} (10\text{V})$ Accuracy $\pm 0.2\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - 0.2 " (5.08mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 60 \text{ PSI} (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Operating Pressure	±30 PSI (±206.84 kPa)
Accuracy ±0.2% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output Type	Wheatstone Bridge
Voltage - Supply 2.5 V ~ 16 V Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output	$0 \text{ mV} \sim 100 \text{ mV} (10 \text{ V})$
Port Size Male - 0.2" (5.08mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Accuracy	±0.2%
Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Voltage - Supply	2.5 V ~ 16 V
FeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure ± 60 PSI (± 413.69 kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package-	Port Size	Male - 0.2" (5.08mm) Tube
Termination Style PC Pin Maximum Pressure ± 60 PSI (± 413.69 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package -	Port Style	Barbless
Maximum Pressure ± 60 PSI (± 413.69 kPa)Operating Temperature -40° C ~ 85° CPackage / Case 4 -SIP ModuleSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±60 PSI (±413.69 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors

26PCDFA6G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

26PCDFA6G Payment Methods





















26PCDFA6G Shipping Methods













If you have any question about 26PCDFA6G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com