



26PCFFH6G Information



For Reference Only

Part Number 26PCFFH6G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR DIFFERENTIAL +-100 PSI

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









26PCFFH6G Specifications

Manufacturer Part Number 26PCFFH6G Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±100 PSI (±689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.6% Voltage - Supply 2.5 V ~ 16 V Port Size Male - M5 Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - Report errors?		
CategorySensors, TransducersPackage4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±100 PSI (±689.48 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.6%Voltage - Supply2.5 V ~ 16 VPort SizeMale - M5Port StyleThreadedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±200 PSI (±1378.95 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	26PCFFH6G
Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±100 PSI (±689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.6% Voltage - Supply 2.5 V ~ 16 V Port Size Male - M5 Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±100 PSI (±689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.6% Voltage - Supply 2.5 V ~ 16 V Port Size Male - M5 Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Category	Sensors, Transducers
Series26PCPressure TypeCompoundOperating Pressure±100 PSI (±689.48 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.6%Voltage - Supply2.5 V ~ 16 VPort SizeMale - M5Port StyleThreadedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±200 PSI (±1378.95 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeCompoundOperating Pressure $\pm 100 \text{ PSI } (\pm 689.48 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 100 \text{ mV } (10\text{ V})$ Accuracy $\pm 0.6\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - M5Port StyleThreadedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 200 \text{ PSI } (\pm 1378.95 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4 - \text{SIP Module}$ Supplier Device Package-	Package	4-SIP Module
Operating Pressure ±100 PSI (±689.48 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV (10V) Accuracy ±0.6% Voltage - Supply 2.5 V ~ 16 V Port Size Male - M5 Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Series	26PC
Output TypeWheatstone BridgeOutput0 mV ~ 100 mV (10V)Accuracy±0.6%Voltage - Supply2.5 V ~ 16 VPort SizeMale - M5Port StyleThreadedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±200 PSI (±1378.95 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Pressure Type	Compound
Output $0 \text{ mV} \sim 100 \text{ mV} (10\text{V})$ Accuracy $\pm 0.6\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - M5Port StyleThreadedFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 200 \text{ PSI} (\pm 1378.95 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Operating Pressure	±100 PSI (±689.48 kPa)
Accuracy ±0.6% Voltage - Supply 2.5 V ~ 16 V Port Size Male - M5 Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output Type	Wheatstone Bridge
Voltage - Supply 2.5 V ~ 16 V Port Size Male - M5 Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output	$0 \text{ mV} \sim 100 \text{ mV} (10 \text{V})$
Port Size Male - M5 Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Accuracy	±0.6%
Port Style Threaded Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Voltage - Supply	2.5 V ~ 16 V
Features Temperature Compensated Termination Style PC Pin Maximum Pressure ±200 PSI (±1378.95 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Port Size	Male - M5
Termination Style PC Pin Maximum Pressure ± 200 PSI (± 1378.95 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package	Port Style	Threaded
Maximum Pressure $\pm 200 \text{ PSI } (\pm 1378.95 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package $-$	Features	Temperature Compensated
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±200 PSI (±1378.95 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

26PCFFH6G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

26PCFFH6G Payment Methods





















26PCFFH6G Shipping Methods













If you have any question about 26PCFFH6G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com