



## **26PCGFA6G Information**



For Reference Only

Part Number 26PCGFA6G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR VACUUM GAUGE +-250 PSI

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **26PCGFA6G Specifications**

Manufacturer Part Number26PCGFA6GManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±250 PSI (±1723.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 150 mV (10V)Accuracy±0.7%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±500 PSI (±3447.38 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-Report errors?		
CategorySensors, TransducersPackage4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±250 PSI (±1723.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 150 mV (10V)Accuracy±0.7%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±500 PSI (±3447.38 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	26PCGFA6G
Package         4-SIP Module           Series         26PC           Pressure Type         Compound           Operating Pressure         ±250 PSI (±1723.69 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 150 mV (10V)           Accuracy         ±0.7%           Voltage - Supply         2.5 V ~ 16 V           Port Size         Male - 0.2" (5mm) Tube           Port Style         Barbless           Features         Temperature Compensated           Termination Style         PC Pin           Maximum Pressure         ±500 PSI (±3447.38 kPa)           Operating Temperature         -40°C ~ 85°C           Package / Case         4-SIP Module           Supplier Device Package         -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package4-SIP ModuleSeries26PCPressure TypeCompoundOperating Pressure±250 PSI (±1723.69 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 150 mV (10V)Accuracy±0.7%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±500 PSI (±3447.38 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Category	Sensors, Transducers
Series         26PC           Pressure Type         Compound           Operating Pressure         ±250 PSI (±1723.69 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 150 mV (10V)           Accuracy         ±0.7%           Voltage - Supply         2.5 V ~ 16 V           Port Size         Male - 0.2" (5mm) Tube           Port Style         Barbless           Features         Temperature Compensated           Termination Style         PC Pin           Maximum Pressure         ±500 PSI (±3447.38 kPa)           Operating Temperature         -40°C ~ 85°C           Package / Case         4-SIP Module           Supplier Device Package         -		Pressure Sensors, Transducers
Pressure TypeCompoundOperating Pressure $\pm 250 \text{ PSI } (\pm 1723.69 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 150 \text{ mV } (10\text{ V})$ Accuracy $\pm 0.7\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - $0.2$ " (5mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 500 \text{ PSI } (\pm 3447.38 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Package	4-SIP Module
Operating Pressure	Series	26PC
Output TypeWheatstone BridgeOutput0 mV ~ 150 mV (10V)Accuracy±0.7%Voltage - Supply2.5 V ~ 16 VPort SizeMale - 0.2" (5mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure±500 PSI (±3447.38 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Pressure Type	Compound
Output $0 \text{ mV} \sim 150 \text{ mV} (10\text{V})$ Accuracy $\pm 0.7\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - $0.2$ " (5mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePC PinMaximum Pressure $\pm 500 \text{ PSI} (\pm 3447.38 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Operating Pressure	±250 PSI (±1723.69 kPa)
Accuracy $\pm 0.7\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size Male - $0.2''$ (5mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PC Pin Maximum Pressure $\pm 500 \text{ PSI } (\pm 3447.38 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package	Output Type	Wheatstone Bridge
Voltage - Supply  2.5 V ~ 16 V  Port Size  Male - 0.2" (5mm) Tube  Port Style  Barbless  Features  Temperature Compensated  Termination Style  PC Pin  Maximum Pressure  ±500 PSI (±3447.38 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  4-SIP Module  Supplier Device Package	Output	$0 \text{ mV} \sim 150 \text{ mV} (10\text{V})$
Port Size  Male - 0.2" (5mm) Tube  Port Style  Barbless  Features  Temperature Compensated  Termination Style  PC Pin  Maximum Pressure  ±500 PSI (±3447.38 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  4-SIP Module  Supplier Device Package	Accuracy	±0.7%
Port Style Barbless Features Temperature Compensated  Termination Style PC Pin  Maximum Pressure ±500 PSI (±3447.38 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package -	Voltage - Supply	2.5 V ~ 16 V
Features Temperature Compensated  Termination Style PC Pin  Maximum Pressure ±500 PSI (±3447.38 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package	Port Size	Male - 0.2" (5mm) Tube
Termination Style PC Pin  Maximum Pressure ±500 PSI (±3447.38 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package -	Port Style	Barbless
Maximum Pressure $\pm 500$ PSI ( $\pm 3447.38$ kPa)Operating Temperature $-40^{\circ}$ C ~ $85^{\circ}$ CPackage / Case $4$ -SIP ModuleSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -40°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package -	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±500 PSI (±3447.38 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors

### **26PCGFA6G Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **26PCGFA6G Payment Methods**





















## **26PCGFA6G Shipping Methods**













If you have any question about 26PCGFA6G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com