

27211218000 Information



For Reference Only

Part Number 27211218000 **Manufacturer** HARTING

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description HLNK SV FE SDP 29 AUS4 HT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









27211218000 Specifications

Manufacturer Part Number 27211218000 Manufacturer HARTING Category Connectors, Interconnects Package - Series Har-link? Connector Type - Contact Type Female Socket Style Board to Cable/Wire Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C Material Flammability Rating UL94 V-0			
Category Connectors, Interconnects Package - Series Har-link? Connector Type - Contact Type Female Socket Style Board to Cable/Wire Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	27211218000	
Package-SeriesHar-link?Connector Type-Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorNaturalInsulation Height0.453" (11.50mm)Contact Length - Post0.114" (2.90mm)Operating Temperature-55°C ~ 125°C	Manufacturer	HARTING	
Package - Series Har-link? Connector Type - Contact Type Female Socket Style Board to Cable/Wire Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects	
Series Har-link? Connector Type - Contact Type Female Socket Style Board to Cable/Wire Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector Type-Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorNaturalInsulation Height0.453" (11.50mm)Contact Length - Post0.114" (2.90mm)Operating Temperature-55°C ~ 125°C	Package	-	
Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorNaturalInsulation Height0.453" (11.50mm)Contact Length - Post0.114" (2.90mm)Operating Temperature-55°C ~ 125°C	Series	Har-link?	
Style Board to Cable/Wire Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Connector Type	-	
Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket	
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorNaturalInsulation Height0.453" (11.50mm)Contact Length - Post0.114" (2.90mm)Operating Temperature-55°C ~ 125°C	Style	Board to Cable/Wire	
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorNaturalInsulation Height0.453" (11.50mm)Contact Length - Post0.114" (2.90mm)Operating Temperature-55°C ~ 125°C	Number of Positions	10	
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorNaturalInsulation Height0.453" (11.50mm)Contact Length - Post0.114" (2.90mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All	
Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)	
Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Number of Rows	2	
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)	
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Insulation Height Ontact Length - Post Operating Temperature Gold Old Old Output Old Old Old Old Old Old Old Ol	Termination	Solder	
Contact Finish Thickness - Mating Insulation Color Natural Insulation Height 0.453" (11.50mm) Contact Length - Post 0.114" (2.90mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull	
Insulation ColorNaturalInsulation Height $0.453"$ ($11.50mm$)Contact Length - Post $0.114"$ ($2.90mm$)Operating Temperature -55° C ~ 125° C	Contact Finish - Mating	Gold	
Insulation Height $0.453'' (11.50 \text{mm})$ Contact Length - Post $0.114'' (2.90 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	-	
Contact Length - Post $0.114'' (2.90 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Natural	
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.453" (11.50mm)	
	Contact Length - Post	0.114" (2.90mm)	
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C	
	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	-	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	Board Guide, Shielding Pins	
		Report errors?

27211218000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

27211218000 Payment Methods



















27211218000 Shipping Methods













If you have any question about 27211218000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com