

### 2766685 Information



For Reference Only

Part Number 2766685

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

**Description** CONSTANT VOLT SOURCE 10VDC

Package Modul

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 2766685 Specifications

Manufacturer Part Number         2766685           Manufacturer         Phoenix Contact           Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         18V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         30mA           Power (Watts)         300mW           Applications         -           Operating Temperature         -20°C ~ 65°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)		
Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         18V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         30mA           Power (Watts)         300mW           Applications         -           Operating Temperature         -20°C ~ 65°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Manufacturer Part Number	2766685
Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         18V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         30mA           Power (Watts)         30mW           Applications         -           Operating Temperature         -20°C ~ 65°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Manufacturer	Phoenix Contact
Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         18V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         30mA           Power (Watts)         300mW           Applications         -           Operating Temperature         -20°C ~ 65°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Type         Isolated           Voltage - Input (Min)         18V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         30mA           Power (Watts)         300mW           Applications         -           Operating Temperature         -20°C ~ 65°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)		DC DC Converters
Type         Isolated           Voltage - Input (Min)         18V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         30mA           Power (Watts)         300mW           Applications         -           Operating Temperature         -20°C ~ 65°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Package	Module
Voltage - Input (Min)       18V         Voltage - Input (Max)       30V         Number of Outputs       1         Voltage - Output 1       10V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       30mA         Power (Watts)       300mW         Applications       -         Operating Temperature       -20°C ~ 65°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Series	-
Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         30mA           Power (Watts)         300mW           Applications         -           Operating Temperature         -20°C ~ 65°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Type	Isolated
Number of Outputs       1         Voltage - Output 1       10V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       30mA         Power (Watts)       300mW         Applications       -         Operating Temperature       -20°C ~ 65°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Voltage - Input (Min)	18V
Voltage - Output 1       10V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       30mA         Power (Watts)       300mW         Applications       -         Operating Temperature       -20°C ~ 65°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Voltage - Input (Max)	30V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30mA Power (Watts) 300mW  Applications - Operating Temperature -20°C ~ 65°C  Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Number of Outputs	1
Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       30mA         Power (Watts)       300mW         Applications       -         Operating Temperature       -20°C ~ 65°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Voltage - Output 1	10V
Voltage - Output 4  Current - Output (Max)  30mA  Power (Watts)  Applications  - Operating Temperature  -20°C ~ 65°C  Efficiency  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension  - Output (Max)  30mA  30mA  30mW  - Company  - Operating Temperature  -20°C ~ 65°C  -20°C ~ 6	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  Operating Temperature  -20°C ~ 65°C  Efficiency  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension  30mA  30mA  30mW  -  DIN Rail  10m	_	-
Power (Watts)  Applications  - Operating Temperature  -20°C ~ 65°C  Efficiency  - Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension  300mW  -20°C ~ 65°C  DIN Rail  100	Voltage - Output 4	-
Applications - Operating Temperature -20°C ~ 65°C  Efficiency - Mounting Type DIN Rail  Package / Case Module  Size / Dimension 4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Current - Output (Max)	30mA
Operating Temperature -20°C ~ 65°C  Efficiency - Mounting Type DIN Rail  Package / Case Module  Size / Dimension 4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Power (Watts)	300mW
Efficiency -  Mounting Type DIN Rail  Package / Case Module  Size / Dimension 4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Applications	-
Mounting Type DIN Rail Package / Case Module Size / Dimension 4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Operating Temperature	-20°C ~ 65°C
Package / Case         Module           Size / Dimension         4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Efficiency	-
Size / Dimension 4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)	Mounting Type	DIN Rail
	Package / Case	Module
Report errors?	Size / Dimension	4.51" L x 0.49" W x 3.90" H (114.5mm x 12.5mm x 99mm)
		Report errors?

#### 2766685 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 2766685 Payment Methods





















## 2766685 Shipping Methods













If you have any question about 2766685, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com