

2766821 Information



For Reference Only

Part Number 2766821

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERTER 24V 200MA

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2766821 Specifications

Manufacturer Part Number 2766821 Manufacturer Phoenix Contact Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series - Type Isolated Voltage - Input (Min) 20V Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)		
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series - Type Isolated Voltage - Input (Min) 20V Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Manufacturer Part Number	2766821
Package Module Series - Type Isolated Voltage - Input (Min) 20V Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Manufacturer	Phoenix Contact
Package Module Series - Type Isolated Voltage - Input (Min) 20V Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Type Isolated Voltage - Input (Min) 20V Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)		DC DC Converters
Type Isolated Voltage - Input (Min) 20V Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Package	Module
Voltage - Input (Min) 20V Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Series	-
Voltage - Input (Max) 30V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Type	Isolated
Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Input (Min)	20V
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Input (Max)	30V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Number of Outputs	1
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 200mA Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Operating Temperature O°C ~ 55°C Efficiency Mounting Type DIN Rail Package / Case Module Size / Dimension - Output (Max) 200mA 4.8W And Company Co	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 4.8W Applications Operating Temperature 0°C ~ 55°C Efficiency Mounting Type DIN Rail Package / Case Module Size / Dimension 200mA 4.8W And Divide And And And And And And And And		-
Power (Watts) 4.8W Applications - Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Output 4	-
Applications Operating Temperature 0°C ~ 55°C Efficiency Mounting Type DIN Rail Package / Case Module Size / Dimension	Current - Output (Max)	200mA
Operating Temperature 0°C ~ 55°C Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Power (Watts)	4.8W
Efficiency - Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Applications	-
Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Operating Temperature	0°C ~ 55°C
Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Efficiency	-
Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Mounting Type	DIN Rail
	Package / Case	Module
Report errors?	Size / Dimension	3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)
		Report errors?

2766821 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2766821 Payment Methods





















2766821 Shipping Methods













If you have any question about 2766821, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com