

## 2766821 Information

www.helserief,

For Reference Only

Part Number 2766821

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

**Description** DC/DC CONVERTER 24V 200MA

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **2766821 Specifications**

Manufacturer Part Number         2766821           Manufacturer         Phoenix Contact           Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         20V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20mA           Power (Watts)         4.8W           Applications         -           Operating Temperature         0°C ~ 55°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)		
Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         20V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         200mA           Power (Watts)         4.8W           Applications         -           Operating Temperature         0°C ~ 55°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Manufacturer Part Number	2766821
Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         20V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         200mA           Power (Watts)         4.8W           Applications         -           Operating Temperature         0°C ~ 55°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Manufacturer	Phoenix Contact
Package         Module           Series         -           Type         Isolated           Voltage - Input (Min)         20V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         200mA           Power (Watts)         4.8W           Applications         -           Operating Temperature         0°C ~ 55°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Type         Isolated           Voltage - Input (Min)         20V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         200mA           Power (Watts)         4.8W           Applications         -           Operating Temperature         0°C ~ 55°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)		DC DC Converters
Type         Isolated           Voltage - Input (Min)         20V           Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         200mA           Power (Watts)         4.8W           Applications         -           Operating Temperature         0°C ~ 55°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Package	Module
Voltage - Input (Min)       20V         Voltage - Input (Max)       30V         Number of Outputs       1         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       200mA         Power (Watts)       4.8W         Applications       -         Operating Temperature       0°C ~ 55°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Series	-
Voltage - Input (Max)         30V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         200mA           Power (Watts)         4.8W           Applications         -           Operating Temperature         0°C ~ 55°C           Efficiency         -           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Type	Isolated
Number of Outputs       1         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       200mA         Power (Watts)       4.8W         Applications       -         Operating Temperature       0°C ~ 55°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Input (Min)	20V
Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       200mA         Power (Watts)       4.8W         Applications       -         Operating Temperature       0°C ~ 55°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Input (Max)	30V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       200mA         Power (Watts)       4.8W         Applications       -         Operating Temperature       0°C ~ 55°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Number of Outputs	1
Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       200mA         Power (Watts)       4.8W         Applications       -         Operating Temperature       0°C ~ 55°C         Efficiency       -         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Output 1	24V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  Operating Temperature  O°C ~ 55°C  Efficiency  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension  - Output (Max)  200mA  4.8W  And Company Co	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  4.8W  Applications  Operating Temperature  0°C ~ 55°C  Efficiency  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension  200mA  4.8W  And  Divide And  And  And  And  And  And  And  And		-
Power (Watts) 4.8W  Applications - Operating Temperature 0°C ~ 55°C  Efficiency - Mounting Type DIN Rail  Package / Case Module  Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Voltage - Output 4	-
Applications  Operating Temperature  0°C ~ 55°C  Efficiency  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension	Current - Output (Max)	200mA
Operating Temperature 0°C ~ 55°C  Efficiency -  Mounting Type DIN Rail  Package / Case Module  Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Power (Watts)	4.8W
Efficiency -  Mounting Type DIN Rail  Package / Case Module  Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Applications	-
Mounting Type DIN Rail Package / Case Module Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Operating Temperature	0°C ~ 55°C
Package / Case         Module           Size / Dimension         3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Efficiency	-
Size / Dimension 3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)	Mounting Type	DIN Rail
	Package / Case	Module
Report errors?	Size / Dimension	3.37" L x 0.98" W x 3.11" H (85.5mm x 25mm x 79mm)
		Report errors?

#### 2766821 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 2766821 Payment Methods





















### 2766821 Shipping Methods













If you have any question about 2766821, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com