

### 2834055-4 Information

helecher.com

For Reference Only

**Part Number** 2834055-4

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Solid State Lighting Connectors

**Description** REC, 3P LATCHED POKE-IN WTW CONN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2834055-4 Specifications

Manufacturer       2834055-4         Manufacturer       TE Connectivity AMP Connectors         Category       Connectors, Interconnects         Solid State Lighting Connectors         Package       -         Series       LIGHT-N-LOK         Style       Cable/Wire to Cable/Wire         Connector Type       Receptacle         Number of Positions       3         Mounting Type       Free Hanging (In-Line)         Termination       Poke-In         Pitch       -         Fastening Type       Latch Holder         Features       -         Housing Color       Red         Wire Gauge       16-22 AWG         Contact Material       Copper Alloy         Contact Finish       Tin         Housing Material       Thermoplastic         Operating Temperature       -40°C ~ 105°C		
CategoryConnectors, InterconnectsPackage-SeriesLIGHT-N-LOKStyleCable/Wire to Cable/WireConnector TypeReceptacleNumber of Positions3Mounting TypeFree Hanging (In-Line)TerminationPoke-InPitch-Fastening TypeLatch HolderFeatures-Housing ColorRedWire Gauge16-22 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Manufacturer Part Number	2834055-4
Package - Series LIGHT-N-LOK Style Cable/Wire to Cable/Wire Connector Type Receptacle Number of Positions 3 Mounting Type Free Hanging (In-Line) Termination Poke-In Pitch - Fastening Type Latch Holder Features - Housing Color Red Wire Gauge 16-22 AWG Contact Material Copper Alloy Contact Finish Tin Housing Material Thermoplastic Operating Temperature - Solid State Lighting Connectors  LIGHT-N-LOK Cable/Wire to Cable/Wire Cable Wire to Cable Wire Cable Wire to Cable	Manufacturer	TE Connectivity AMP Connectors
Package-SeriesLIGHT-N-LOKStyleCable/Wire to Cable/WireConnector TypeReceptacleNumber of Positions3Mounting TypeFree Hanging (In-Line)TerminationPoke-InPitch-Fastening TypeLatch HolderFeatures-Housing ColorRedWire Gauge16-22 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Category	Connectors, Interconnects
SeriesLIGHT-N-LOKStyleCable/Wire to Cable/WireConnector TypeReceptacleNumber of Positions3Mounting TypeFree Hanging (In-Line)TerminationPoke-InPitch-Fastening TypeLatch HolderFeatures-Housing ColorRedWire Gauge16-22 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialThermoplasticOperating Temperature-40°C ~ 105°C		Solid State Lighting Connectors
StyleCable/Wire to Cable/WireConnector TypeReceptacleNumber of Positions3Mounting TypeFree Hanging (In-Line)TerminationPoke-InPitch-Fastening TypeLatch HolderFeatures-Housing ColorRedWire Gauge16-22 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Package	-
Connector Type Receptacle  Number of Positions 3  Mounting Type Free Hanging (In-Line)  Termination Poke-In  Pitch - Fastening Type Latch Holder  Features - Housing Color Red Wire Gauge 16-22 AWG  Contact Material Contact Finish Tin  Housing Material Operating Temperature Receptacle Receptacle Red Receptacle Red Anotherial Copper Alloy Thermoplastic -40°C ~ 105°C	Series	LIGHT-N-LOK
Number of Positions3Mounting TypeFree Hanging (In-Line)TerminationPoke-InPitch-Fastening TypeLatch HolderFeatures-Housing ColorRedWire Gauge16-22 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Style	Cable/Wire to Cable/Wire
Mounting TypeFree Hanging (In-Line)TerminationPoke-InPitch-Fastening TypeLatch HolderFeatures-Housing ColorRedWire Gauge16-22 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Connector Type	Receptacle
Termination Poke-In  Pitch -  Fastening Type Latch Holder  Features -  Housing Color Red  Wire Gauge 16-22 AWG  Contact Material Copper Alloy  Contact Finish Tin  Housing Material Thermoplastic  Operating Temperature -40°C ~ 105°C	Number of Positions	3
Pitch - Latch Holder Features - Housing Color Red Wire Gauge 16-22 AWG Contact Material Copper Alloy Contact Finish Tin Housing Material Thermoplastic Operating Temperature - 40°C ~ 105°C	Mounting Type	Free Hanging (In-Line)
Fastening Type  Features  - Housing Color  Red  Wire Gauge  16-22 AWG  Contact Material  Copper Alloy  Contact Finish  Tin  Housing Material  Thermoplastic  Operating Temperature  Latch Holder  -  Latch Holder  Latch Holder  Features  -  Latch Holder  Fred  Red  16-22 AWG  Copper Alloy  Tin  Thermoplastic  -40°C ~ 105°C	Termination	Poke-In
Features - Housing Color Red Wire Gauge 16-22 AWG Contact Material Copper Alloy Contact Finish Tin Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Pitch	-
Housing Color  Red  Wire Gauge  16-22 AWG  Contact Material  Copper Alloy  Contact Finish  Tin  Housing Material  Thermoplastic  Operating Temperature  Red  16-22 AWG  Copper Alloy  Tin  Thermoplastic  -40°C ~ 105°C	Fastening Type	Latch Holder
Wire Gauge $16\text{-}22 \text{ AWG}$ Contact MaterialCopper AlloyContact FinishTinHousing MaterialThermoplasticOperating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Features	-
Contact Material  Copper Alloy  Contact Finish  Tin  Housing Material  Operating Temperature  Copper Alloy  Tin  Thermoplastic  -40°C ~ 105°C	Housing Color	Red
Contact Finish Tin  Housing Material Thermoplastic  Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Wire Gauge	16-22 AWG
Housing Material Thermoplastic  Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material	Copper Alloy
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish	Tin
	Housing Material	Thermoplastic
Report errors?	Operating Temperature	-40°C ~ 105°C
		Report errors?

### **2834055-4 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 2834055-4 Payment Methods



















## 2834055-4 Shipping Methods













If you have any question about 2834055-4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com