

2866336 Information



For Reference Only

Part Number 2866336

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 100W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2866336 Specifications

Manufacturer Part Number 2866336 Manufacturer Phoenix Contact Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MINI Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MINI Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Manufacturer Part Number	2866336
Package - Series MINI Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Manufacturer	Phoenix Contact
Package - Series MINI Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MINI Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Package	-
Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Series	MINI
Voltage - Input 100 ~ 240 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Type	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 24V 4V 4V 4V 4V 4V 4V 4V 4V 4	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension - Current - Output (Max)	Voltage - Input	100 ~ 240 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension - 25°C ~ 70°C (W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) 3.8A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Voltage - Output 2	-
Current - Output (Max) 3.8A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Current - Output (Max)	3.8A
Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Power (Watts)	100W
Efficiency 88% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Applications	ITE (Commercial)
Operating Temperature -25°C ~ 70°C (With Derating) Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, Load Sharing, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Efficiency	88%
Mounting Type DIN Rail Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Operating Temperature	-25°C ~ 70°C (With Derating)
Size / Dimension 4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)	Features	Adjustable Output, Load Sharing, PFC, Universal Input
	Mounting Type	DIN Rail
Report errors?	Size / Dimension	4.21" L x 2.66" W x 3.90" H (107.0mm x 67.5mm x 99.0mm)
		Report errors?

2866336 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2866336 Payment Methods





















2866336 Shipping Methods













If you have any question about 2866336, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com