

## 2866530 Information



For Reference Only

Part Number 2866530

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

**Description** DC/DC CONVERTER 24V 480W

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2866530 Specifications

Manufacturer Part Number         2866530           Manufacturer         Phoenix Contact           Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         Module           Series         TRIO           Type         Isolated           Voltage - Input (Min)         450V           Voltage - Input (Max)         840V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Operating Temperature         -25°C ~ 70°C           Efficiency         91%           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)           Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         Module           Series         TRIO           Type         Isolated           Voltage - Input (Min)         450V           Voltage - Input (Max)         840V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Operating Temperature         -25°C ~ 70°C           Efficiency         91%           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Manufacturer Part Number	2866530
Package         Module           Series         TRIO           Type         Isolated           Voltage - Input (Min)         450V           Voltage - Input (Max)         840V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Operating Temperature         -25°C ~ 70°C           Efficiency         91%           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Manufacturer	Phoenix Contact
Package         Module           Series         TRIO           Type         Isolated           Voltage - Input (Min)         450V           Voltage - Input (Max)         840V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Operating Temperature         -25°C ~ 70°C           Efficiency         91%           Mouting Type         DIN Rail           Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         TRIO           Type         Isolated           Voltage - Input (Min)         450V           Voltage - Input (Max)         840V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Operating Temperature         -25°C ~ 70°C           Efficiency         91%           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)		DC DC Converters
Type         Isolated           Voltage - Input (Min)         450V           Voltage - Input (Max)         840V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Operating Temperature         -25°C ~ 70°C           Efficiency         91%           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Package	Module
Voltage - Input (Min)       450V         Voltage - Input (Max)       840V         Number of Outputs       1         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       480W         Applications       ITE (Commercial)         Operating Temperature       -25°C ~ 70°C         Efficiency       91%         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Series	TRIO
Voltage - Input (Max)         840V           Number of Outputs         1           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Operating Temperature         -25°C ~ 70°C           Efficiency         91%           Mounting Type         DIN Rail           Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Туре	Isolated
Number of Outputs       1         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       480W         Applications       ITE (Commercial)         Operating Temperature       -25°C ~ 70°C         Efficiency       91%         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Voltage - Input (Min)	450V
Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       480W         Applications       ITE (Commercial)         Operating Temperature       -25°C ~ 70°C         Efficiency       91%         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Voltage - Input (Max)	840V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       480W         Applications       ITE (Commercial)         Operating Temperature       -25°C ~ 70°C         Efficiency       91%         Mounting Type       DIN Rail         Package / Case       Module         Size / Dimension       6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Number of Outputs	1
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -25°C ~ 70°C  Efficiency  91%  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension	Voltage - Output 1	24V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -25°C ~ 70°C  Efficiency  91%  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -25°C ~ 70°C  Efficiency  91%  Mounting Type  DIN Rail  Package / Case  Module  Size / Dimension  20A  480W  DIN Exploit (Commercial)  -25°C ~ 70°C  DIN Rail  DIN Rail  Mounting Type  Module  Size / Dimension  6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Voltage - Output 3	-
Power (Watts) 480W  Applications ITE (Commercial)  Operating Temperature -25°C ~ 70°C  Efficiency 91%  Mounting Type DIN Rail  Package / Case Module  Size / Dimension 6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Operating Temperature -25°C ~ 70°C  Efficiency 91%  Mounting Type DIN Rail  Package / Case Module  Size / Dimension 6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Current - Output (Max)	20A
Operating Temperature -25°C ~ 70°C  Efficiency 91%  Mounting Type DIN Rail  Package / Case Module  Size / Dimension 6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Power (Watts)	480W
Efficiency 91%  Mounting Type DIN Rail  Package / Case Module  Size / Dimension 6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Applications	ITE (Commercial)
Mounting Type DIN Rail Package / Case Module Size / Dimension 6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Operating Temperature	-25°C ~ 70°C
Package / Case         Module           Size / Dimension         6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Efficiency	91%
Size / Dimension 6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)	Mounting Type	DIN Rail
	Package / Case	Module
Report errors?	Size / Dimension	6.00" L x 4.53" W x 5.12" H (152.5mm x 115.0mm x 130.0mm)
		Report errors?

### 2866530 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 2866530 Payment Methods





















## 2866530 Shipping Methods













If you have any question about 2866530, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com